

## OMNITRONIC WAMS-04P Wireless PA system

Portable PA system with VHF receiver unit and CD/MP3 player

Art. No.: 13106983

GTIN: 4026397476583



**The article is no longer in our assortment.**

### Features:

- Portable amplifier system with integrated VHF receiver unit and matching wireless microphone
- Wireless operation with fixed VHF frequency 202.950 MHz
- Matching pocket transmitter TM-200A optional
- Ideal for all mains independent and wireless applications like speeches, conferences, presentations, sales events etc.
- Easy transportation via telescopic trolley handle, 2 wheels and transport handle
- Operation via mains, built-in rechargeable lead gel batteries for up to 4 hours operating time (integrated automatic charging of the batteries) or external 18 V source
- CD/MP3 Player with anti-shock, pitch control and IR remote control
- SD card reader and USB interface for external storage media
- ID3 tag indication, folder navigation, random play, repeat functions, title programming
- Tape deck
- High-capacity bass reflex speaker system (2 x 20 cm woofer)
- Connections for the combination of several amplifier systems
- 3 independently adjustable microphone inputs (6.3 mm jack)
- 1 adjustable line input (6.3 mm jack)
- Microphone channels with switchable talkover function and adjustable echo
- 1 line output, 1 aux output (both 6.3 mm jack)
- 1 recording output (stereo RCA)
- Enclosure with scratch-resistant lacquer surface, impact-resistant steel grille and flange for speaker distance tube
- License required
- Cordless, flexible and versatile
- Battery operation up to 4h depending on program used

### Logistic

EAN / GTIN: 4026397476583

Weight: 22,00 kg

Length: 0.47 m

Width: 0.47 m

Height: 0.76 m

## Technical specifications:

Power supply:	230 V AC, 50 Hz
Power consumption:	110,00 W
Battery pack type:	3 x lead 6 V, 7000 mAh,
Battery pack:	Battery operation up to 4h depending on program used Recharging time 7h
Battery:	2 x 1.5 V AA Mignon R06 zinc carbon included
Frequency range:	80 - 13000 Hz
Dimensions:	Width: 35 cm Depth: 30 cm Height: 57,5 cm
	or 18 V DC via built-in lead gel rechargeable batteries or external source
Battery type:	3 x 6 V/7 Ah, removable
Battery operation:	2-4 hours
Recharging time:	7-10 hours
Dimensions (H x W x D):	575 x 350 x 300 mm
Weight:	18 kg
Amplifier:	
Nominal power output:	60 W RMS/ 4 ohms
Maximum power output:	100 W/ 4 ohms
Min. input sensitivity:	0.775 V
Distortion:	0.5 %
Connection:	
Inputs:	3 x microphone/1 x aux (6.3 mm jack bal./unbal.)
Outputs:	1 x line/1 x aux (6.3 mm jack bal./unbal.), 1 x record (stereo RCA)
Speaker system:	
Rated power:	2 x 30 W RMS
Program power:	100 W
Components:	2 x 20 cm woofer (2 x 8")
Sensitivity:	90 dB
Maximum SPL:	95 dB
Impedance:	4 ohms
Wireless receiver:	
System:	Non-diversity, one channel
Carrier frequency:	VHF 202.950 MHz
Frequency stability:	±0.005 %
S/N ratio:	>60 dB
Input sensitivity:	10 dB
Dynamic range:	>100 dB
Modulation method:	FM
Coverage:	approx. 50 m (with line-of-sight)

CD/MP3 player:	CD/-R in CD-DA and MP3 formats
Available storage media:	SD(HC) cards and USB devices up to 32 GB (FAT32)

---