

OMNITRONIC WAMS-10BT1 Wireless PA System

Portable PA system with UHF receiver unit, audio player, Bluetooth and 75 W RMS

Art. No.: 13106995 GTIN: 4026397516203











The article is no longer in our assortment.

Features:

- Portable all-in-one PA system for mobile use
- Ideal for mains independent and wireless applications, e.g. at sales events, lectures and gyms
- 3-channel power mixer (75 W RMS) and 2-way speaker system with a 25 cm woofer (10")
- Power-efficient and battery-saving class D amplifier
- MP3 player with Bluetooth receiver and IR remote control
- SD card slot and USB input
- Stream music wirelessly from your mobile devices (e.g. smartphone, tablet) via Bluetooth
- UHF receiver unit and matching wireless microphone
- Mains operation or battery operation for up to 12 hours of music playing
- Integrated automatic charging of the battery
- Rechargeable batteries optionally available (13106994)
- 2 mono input channels mic/line with adjustable reverb effect
- 1 stereo input channel switchable between internal MP3 player and line signal sources e.g. CD players and notebook
- Common 2-band EQ for highs and lows
- Link output for the combination of several amplifier systems
- Light-weight black plastic enclosure with metal grille and carrying handle
- Operation of the hand-held microphone via 2 x AA batteries (not included)
- Flange for speaker stand installation etc.
- Two wheels and retractable pulling handle for trolley-like mobility
- Matching pocket transmitter and set for adding a second wireless channel available as accessory
- License-free and approved in the EU
- Cordless, flexible and versatile
- Battery operation up to 12h depending on program used microphone

Logistic

EAN / GTIN: 4026397516203

Weight: 15,55 kg Length: 0.42 m Width: 0.37 m Heigth: 0.64 m

Technical specifications:

| built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: stereo RCA and 3.5 mm jack Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | <u> </u> | |
|--|---------------------------|---|
| Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Battery pack Battery pack type: 2 x lead 12 V, Battery pack: Battery operation up to 12h depending on program used Recharging time 7h Type of speaker: Wireless PA system Dimensions: Width: 36 cm Depth: 32 cm Height: 56 cm Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x 1.5 V AA Mignon LR06 alkaline mangane: included Frequency range: 55 - 18000 Hz Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplifier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Speaker system: Components: 25 cm woofer (10°), 2.5 cm compression driver (1°) (1°) Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Power supply: | 100-240 V AC, 50/60 Hz |
| version power supply cord with safety plug (provided) Battery/battery pack Battery pack type: 2 x lead 12 V, Battery pack: Battery operation up to 12h depending on program used Recharging time 7h Type of speaker: Wireless PA system Dimensions: Width: 36 cm Depth: 32 cm Height: 56 cm Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x 1.5 V AA Mignon LR06 alkaline mangane: included Frequency range: 55 - 18000 Hz Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplifier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Speaker system: Components: 25 cm woofer (10°), 2.5 cm compression driver (1°) (1°) Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Power consumption: | 175,00 W |
| Battery pack type: 2 x lead 12 V, Battery pack: Battery pack: Battery operation up to 12h depending on program used Recharging time 7h Type of speaker: Wireless PA system Dimensions: Width: 36 cm Depth: 32 cm Height: 56 cm Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x 1.5 V AA Mignon LR06 alkaline manganer included Frequency range: 55 - 18000 Hz Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC, 5 Ah Battery operation: Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplifier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Speaker system: Components: 25 cm woofer (10°), 2.5 cm compression driver (1°) Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Power connection: | version power supply cord with safety plug |
| Battery pack: Battery operation up to 12h depending on program used Recharging time 7h Type of speaker: Wireless PA system Dimensions: Width: 36 cm Depth: 32 cm Height: 56 cm Cardioid Battery: 2 x 1.5 V AA Mignon LR06 alkaline mangane: included Frequency range: 55 - 18000 Hz Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | | Battery/battery pack |
| program used Recharging time 7h Type of speaker: Wireless PA system Dimensions: Width: 36 cm Depth: 32 cm Height: 56 cm Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x 1.5 V AA Mignon LR06 alkaline mangane: included Frequency range: 55 - 18000 Hz Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Uine, stereo: stereo RCA and 3.5 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Battery pack type: | 2 x lead 12 V, |
| Type of speaker: Wireless PA system Dimensions: Width: 36 cm Depth: 32 cm Height: 56 cm Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x 1.5 V AA Mignon LR06 alkaline mangane: included Frequency range: 55 - 18000 Hz Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: stereo RCA and 3.5 mm jack Cutput: Line, mono: 6.3 mm jack Speaker system: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB | Battery pack: | program used |
| Dimensions: Width: 36 cm Depth: 32 cm Height: 56 cm Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x 1.5 V AA Mignon LR06 alkaline manganer included Frequency range: 55 - 18000 Hz Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium manganer built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Unine, stereo: Stereo RCA and 3.5 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | | Recharging time 7h |
| Depth: 32 cm Height: 56 cm | Type of speaker: | Wireless PA system |
| Height: 56 cm | Dimensions: | |
| Capsule type: Dynamic Polar pattern: Cardioid Battery: 2 x 1.5 V AA Mignon LR06 alkaline manganes included Frequency range: 55 - 18000 Hz Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: stereo RCA and 3.5 mm jack Output: Line, mono: Line, mono: 6.3 mm jack Speaker system: 25 cm woofer (10°), 2.5 cm compression driver (1°) Components: 25 cm woofer (10°), 2.5 cm compression driver (1°) | | |
| Polar pattern: Cardioid Battery: 2 x 1.5 V AA Mignon LR06 alkaline manganet included Frequency range: 55 - 18000 Hz Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: stereo RCA and 3.5 mm jack Output: Line, mono: 6.3 mm jack Speaker system: 25 cm woofer (10"), 2.5 cm compression driver (1") Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB | Capsule type: | |
| Battery: 2 x 1.5 V AA Mignon LR06 alkaline manganet included Frequency range: 55 - 18000 Hz Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | | |
| Included | | |
| Switch: On/off switch; mute control Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | ballery. | |
| Battery: 1 x button cell 3.0 V CR2025 lithium mangane built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: ottoput: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Frequency range: | 55 - 18000 Hz |
| built-in or 2 x 12 V DC via rechargeable batteries Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: stereo RCA and 3.5 mm jack Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Switch: | On/off switch; mute control |
| Rec. battery (accessory): 2 x 12 V DC, 5 Ah Battery operation: 12 hours Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Stereo RCA and 3.5 mm jack Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Battery operation: Recharging time: 7-9 hours Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Stereo RCA and 3.5 mm jack Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | | or 2 x 12 V DC via rechargeable batteries |
| Recharging time: Dimensions (H x W x D): 320 x 360 x 560 mm Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Rec. battery (accessory): | 2 x 12 V DC, 5 Ah |
| Dimensions (H x W x D): Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Battery operation: | 12 hours |
| Weight: 17 kg Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: stereo RCA and 3.5 mm jack Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Recharging time: | 7-9 hours |
| Amplfier: Nominal power output: 75 W RMS Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Output: Line, mono: 5.3 mm jack Components: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Dimensions (H x W x D): | 320 x 360 x 560 mm |
| Nominal power output: Maximum power output: 150 W Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Output: Line, mono: 5 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Weight: | 17 kg |
| Maximum power output: Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Output: Line, mono: 5 peaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Amplfier: | |
| Inputs: Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Nominal power output: | 75 W RMS |
| Mic/Line, mono: 2 x combination XLR/6.3 mm jack Line, stereo: Stereo RCA and 3.5 mm jack Output: Line, mono: 6.3 mm jack Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Maximum power output: | 150 W |
| Line, stereo: Output: Line, mono: Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Inputs: | |
| Output: Line, mono: Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Mic/Line, mono: | 2 x combination XLR/6.3 mm jack |
| Line, mono: Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Line, stereo: | stereo RCA and 3.5 mm jack |
| Speaker system: Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Output: | |
| Components: 25 cm woofer (10"), 2.5 cm compression driver (1") Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Line, mono: | 6.3 mm jack |
| Maximum SPL: 106 dB Sensitivity: 90 dB Reception module: | Speaker system: | |
| Sensitivity: 90 dB Reception module: | Components: | 25 cm woofer (10"), 2.5 cm compression driver (1") |
| Reception module: | Maximum SPL: | 106 dB |
| | Sensitivity: | 90 dB |
| Corrier fraguency | Reception module: | |
| Camer requency: UHF 863-865 MHZ | Carrier frequency: | UHF 863-865 MHz |

| Range: | approx. 30 m |
|--------------------------|--|
| Wireless microphones: | |
| Frequency stability: | ±0.005 % |
| RF power output: | 10 mW |
| Polar pattern: | omnidirectional |
| Range: | approx. 30 m |
| Battery: | 2 x 1.5 V AA |
| Battery life: | 13 hours |
| Dimensions (D x L): | 40 x 260 mm |
| Weight: | 250 g |
| Bluetooth: | |
| Carrier frequency: | 2.4 GHz |
| Range: | approx. 10 m |
| Audio player: | |
| Playback format: | MP3, WMA |
| Available storage media: | USB devices and SD(HC) cards up to 32 GB |
| File system: | FAT32 |