



### Features:

#### EUROLITE LED TMH-12 Moving Head Beam

4in1 moving head with narrow beam angle

- Equipped with 12 high-power 10 W RGBW CREE LEDs (4in1)
- Compact lightweight
- Narrow beam angle
- Positioning within 630° PAN and 200° TILT
- Stepless RGBW color mixture
- Different dimmer speeds (step response) adjustable
- Masterdimmer
- 8 internal programs can be called up via Control board
- Color-macro-function for an easy selection of possible color-combinations
- Strobe effect with 1-18 flashes per second
- Random strobe effect
- Exact positioning via 16 bit PAN/TILT movement resolution
- Automatic position correction
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Sound-control via built-in microphone
- Control board with graphic LCD for adjusting the DMX-starting address, PAN/TILT reverse, program, reset, operating hours
- Switch-mode power supply
- Automatic power supply adaption between 100 and 240 Volts without power selector
- DMX control via every standard DMX controller
- 12 LEDs 10 W high-power 4in1 RGBW (homogenous color mix)
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Gobo effect

### Logistic

- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- With a beam angle of 9°

### **ROADINGER Flightcase 4x TMH-12**

Flightcase for four TMH-12 spots

- Interior suitable for four TMH-12 Moving-Heads
- With two additional storage compartments
- Interior and cover (not removable) upholstered with foam
- High-quality workmanship with 8 mm multiplex birch wood, black laminated
- Aluminum profile frames (30 mm) with rounded edges
- 4 castors (100 mm), 2 of which with locking brakes
- 4 stacking dishes for stacking the cases
- Three-leg, medium-sized steel ball corners (chrome)
- 2 hinges
- 2 high-quality butterfly locks
- 2 case handles
- Castors
- For further information about this product, please refer to the Data Sheet under "Downloads"

### **EUROLITE DMX Cable XLR 3-pin 10m bk**

High-quality DMX cable

- Adheres to the DMX standard USITT DMX-512/1990/-A
- Very flexible cable
- Electric cable with good shielding
- Robust version
- For building DMX controlled lighting systems, LED spotlights etc.

### **EUROLITE DMX Move Controller 512 PRO**

Console with motorized faders, color & motion effects (24 devices/34 channels)

- DMX controller for DMX light effect units such as moving heads, scanners and LED spot lights with RGBW color mixture
- 512 DMX channels can be assigned and inverted as desired to 34 control channels (softpatch)
- For 24 fixtures with max. 34 control channels each
- USB port for storing program data
- Quick programming thanks to 9 integrated movement patterns and 6 color effects (pan/tilt position, fade time and running time adjustable)
- Several movement patterns and color effects can be used simultaneously
- Manual, time-controlled or sound-controlled chase running mode
- 3 DMX fixture levels can be controlled
- 8 motorized DMX channel faders for user-friendly control
- The motor faders provide a precise overview of the parameters when switching the individual banks, chases and scenes
- 2 jog wheels for pan/tilt
- Master fader for color and dimmer channels
- Blackout function
- Color-illuminated buttons provide easy orientation
- Can transmit up to 512 DMX channels
- (19") 48.3 cm rack installation 4 U
- Programmable 30 scenes/chases each with 485 cues distributed over 2 page/s
- Control via DMX; RDM
- LCD display
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; stage; mobile djs / entertainer
- Silent operation

### **ROADINGER Mixer Case Pro MCB-19, sloping, bk, 6U**

Rack case

- Upward tilted profile rails for top-operated units

- 6 U
- High-quality workmanship with plywood multi-layer glued 7 mm, black, laminated
- Interior with foam padding
- Removable cover
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 2 high-quality butterfly locks with shut-off function
- Rubber feet
- With profile rails suitable for 19" units
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 49.79 kg

---

### EUROLITE LED TMH-12 Moving Head Beam

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	150 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	12 x 10 W high-power 4in1 RGBW (homogenous color mix)
Max. TILT movement:	200° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	630° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 18 Hz
DMX channels:	12
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512
Beam angle (1/2 peak):	9°
Housing color:	Black
Dimensions:	Width: 25.5 cm Depth: 15.5 cm Height: 31 cm
Weight:	5.10 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### ROADINGER Flightcase 4x TMH-12

Maximum load: 50 kg

---

Transport aid:	Castors
Material:	Plywood multi-layer glued, 8 mm
Color:	Black, laminated
Dimensions:	Width: 60 cm Depth: 49.5 cm Height: 52 cm
Weight:	17.25 kg
Strength:	8 mm
Outside dimensions (W x D x H):	600 x 495 x 520 mm
Inside dimensions (W x D x H):	550 x 440 x 300 mm
Compartment dimensions (W x D x H):	265 x 150 x 300 mm
Accessory compartment (W x D x H):	90 x 550 x 300 mm

#### **EUROLITE DMX Cable XLR 3-pin 10m bk**

Cable length:	10 m
Plug A:	1 x 3-pin XLR (M)
Plug B:	1 x 3-pin XLR (F)
Color:	Black
Weight:	0.51 kg

#### **EUROLITE DMX Move Controller 512 PRO**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Fuse:	5 x 20 mm, F 1.25 A fuse replaceable
Programs:	Programmable 30 scenes/chases each with 485 cues distributed over 2 page/s
DMX channels:	Output 512
DMX output:	1 x 3-pin XLR (F) mounting version
Control:	DMX; RDM
Housing color:	Black
Display type:	LCD display
Available storage media:	USB devices (FAT 32)
USB port:	Type A
Color:	Black
PC connect:	, firmware can be updated
Housing design:	(19") 48.3 cm rack installation 4 U Desktop console housing
Dimensions:	Width: 48.3 cm Depth: 17 cm Height: 8.9 cm
Weight:	3.82 kg

Noise classification: Class 0 (no noise at all)

---

**ROADINGER Mixer Case Pro MCB-19, sloping, bk, 6U**

Maximum load:	25 kg
Removable covers:	1 pc/pcs
Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Transport aid:	Rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Black, laminated
Inside dimensions:	31 cm x 10 cm
Front panel width:	19"
Mounting height:	Approx. 26.5 cm (6 U)
Mounting depth:	100 mm - 180 mm
Housing design:	6 U
Dimensions:	Width: 54.5 cm Depth: 35 cm Height: 24 cm
Weight:	6.30 kg

**Scope of delivery:**

---

**4 x EUROLITE LED TMH-12 Moving Head Beam**

1 x omega bracket

**4 x EUROLITE DMX Cable XLR 3-pin 10m bk**

1 x XLR cable

**1 x EUROLITE DMX Move Controller 512 PRO**

1 x controller  
1 x user manual  
1 x power cord