



Features:

EUROLITE AKKU UP-4 QCL Spot QuickDMX

Bright Uplight with 4 x 8 W 4in1 LED and QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- Battery operation up to 9.5h depending on program used
- Integrated automatic charging of the battery and status indicator
- 4 LEDs 8 W SMD 9080 4in1 RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; Dimmer electronic; color blend stepless; color change adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone
- Flicker-free
- With a beam angle of 22°
- With bracket for floor use
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental
- Silent operation
- Application possibility: Standing

EUROLITE SB-4 Soft Bag M

Black soft bag for up to four devices (AKKU UP-4/TL-3 TCL)

- Practical transport bag offers enough space for several lighting effects and accessories

Logistic

- Large interior, four times divisible and adaptable with foam dividers and pads
- Suitable e.g. for 4 x AKKU UP-4 Spot, 4 x TL-3 TCL Trusslight (41700500) or 3 x AKKU UP-4 Spot QuickDMX (41700540)
- Interior upholstery helps securing and safeguarding the fixtures during transportation
- External pocket stores accessories like cables, clamps, lamps and tape
- Made of easy-care nylon
- Carrying handles

EUROLITE QuickDMX Wireless Transmitter

Compact wireless DMX transmitter 2.4 GHz

- User-friendly 3-pin XLR adapter (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Can transmit up to 512 DMX channels
- Control via QuickDMX; DMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference

Technical specifications:

Weight:	15.02 kg
---------	----------

EUROLITE AKKU UP-4 QCL Spot QuickDMX

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
Protection class:	Protection class I
Power connection:	Battery/battery pack Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1 m
Power output:	1 x P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 14.8 V, 7800 mAh, 115.44 Wh
Battery pack:	Battery operation up to 9.5h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 8 W SMD 9080 4in1 RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
DMX input:	1 x 3-pin XLR (M) mounting version IP
DMX output:	1 x 3-pin XLR (F) mounting version IP
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; IR remote control; sound to light via microphone

Fixtures available for:	Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Projection:	Flicker-free
Carrier frequency:	2.4 GHz
Beam angle (1/2 peak):	22°
Beam angle (1/10 peak):	32°
Housing color:	Black
Attachment system:	Bracket for floor use
Dimensions:	Width: 16.7 cm Depth: 13.8 cm Height: 18.8 cm
Weight:	3.59 kg
Noise classification:	Class 0 (no noise at all)
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-4 Soft Bag M

Maximum load:	25 kg
Material:	Textile
Color:	Black
Compartment dimensions:	14 cm x 14 cm x 19 cm
Inside dimensions:	29 cm x 29 cm x 19 cm
Dimensions:	Width: 30 cm Depth: 33 cm Height: 20 cm
Weight:	0.51 kg

EUROLITE QuickDMX Wireless Transmitter

Power supply:	100-240 V AC, 50/60 Hz 5V DC 1000 mA
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord for USB A mains connection (provided)
DMX channels:	Output 512
DMX input:	1 x 3-pin XLR (M)
Control:	QuickDMX; DMX; plug and play
Range:	Range up to 400m
Carrier frequency:	2.4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Color:	Silver

Dimensions:

Length: 21.2 cm

Diameter: Ø 1.8 cm

Weight:

0.15 kg

Scope of delivery:

4 x EUROLITE AKKU UP-4 QCL Spot QuickDMX

- 1 x spotlight
- 1 x user manual
- 1 x declaration of conformity
- 1 x power cord
- 1 x remote control
- 1 x battery

1 x EUROLITE QuickDMX Wireless Transmitter

- 1 x device
- 1 x user manual
- 1 x declaration of conformity
- 1 x external mains adapter
- 1 x USB cable