

## EUROLITE Set 4x AKKU UP-4 HCL Spot WDMX bk + Case

Art. No.: 20000040

GTIN:







## The article is no longer in our assortment.

Features: Logistic

#### **EUROLITE AKKU UP-4 HCL Spot WDMX bk**

LED Uplight with 4 x 12 W 6in1 LED & wireless DMX receiver (Wireless Solution)

- Compact and bright
- Equipped with 4 x 12 W HCL (hexacolor LED) in red, green, blue, amber, white and UV
- With integrated wireless receiver for WDMX operation (Wireless Solution made in Sweden)
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 8.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- With integrated folding foot for angled placement by floor installation
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 6, 8 or 12 DMX channels selectable
- Functions: static colors, stepless RGBAW+UV color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- DMX control via any standard DMX controller
- Available in 2 housing colors: black and white
- The device is cooled by passive convection cooling
- Control via stand-alone; W-DMX by wireless solution; IR remote control
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain
- Flicker-free

- With a beam angle of 22°

#### device

- Cordless, flexible and versatile
- Battery operation up to 8,5h depending on program used

#### Package contents

- 1 x device, 1 x remote control

#### **ROADINGER Flightcase 4x AKKU UP-4**

Trunk case, PRO version

- Cable bushing allows loading the devices inside
- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Rubber feet

Weight:

- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

16,22 kg

# Technical specifications:

#### **EUROLITE AKKU UP-4 HCL Spot WDMX bk**

| Power supply:           | 100-240 V AC, 50/60 Hz                                     |
|-------------------------|--|
| Power consumption:      | 37 W   |
| IP classification:      | IP20   |
| Lamp type:              | LED lamp   |
| Cooling:                | Passive convection cooling                                 |
| Control:                | Stand-alone; W-DMX by wireless solution; IR remote control |
| Preprogrammed in:       | Light´J; LED PC-Control 512; Light Captain                 |
| Projection:             | Flicker-free   |
| Beam angle:             | 22°  |
| Beam angle (1/2 peak):  | 22°  |
| Beam angle (1/10 peak): | 33°  |
| Housing color:          | Black  |
| Dimensions:             | Width: 13,8 cm<br>Depth: 14,5 cm<br>Height: 19,1 cm        |
| Weight:                 | 2,91 kg  |
| Device                  |  |
| Battery pack type:      | 1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh                 |
| Battery pack:           | Battery operation up to 8,5h depending on program used     |
|                         | Recharging time 4,5h                                       |
|                         |  |

| Battery:                      | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
|-------------------------------|---|
| Battery pack type:            | Li-ion 14.8 V, 6600 mAh (97.68 Wh)                      |
| Battery operation:            | 8.5 hours   |
| Recharging time:              | 4.5 hours   |
| Battery remote control:       | CR2025 button cell 3 V                                  |
| DMX channels:                 | 6/8/12  |
| DMX connection:               | 3-pin XLR   |
| Sound-control:                | via built-in microphone                                 |
| Wireless signal transmission: | 2.4 GHz (ISM)   |
| LED type:                     | 12 W HCL  |
| LED number:                   | 4   |
| Beam angle:                   | 22°   |
| Dimensions (L x W x H):       | 145 x 138 x 191 mm                                      |
| Legal specifications          |   |
| Special product:              | Not designed for household room illumination            |
| Intended use:                 | Show effect lighting                                    |

### **ROADINGER Flightcase 4x AKKU UP-4**

| Maximum load:            | 25 kg                    |
|--------------------------|--------------------------|
| Aluminum profile frames: | 25 mm                    |
| Case handle:             | 1 pc/pcs                 |
| Stop hinge:              | 2 pc/pcs                 |
| Lock:                    | Butterfly lock: 1 pc/pcs |
| Transport aid:           | Rubber feet              |
| Use of brands:           | Branded hardware         |
| Material:                | Birch multiplex, 7 mm    |
| Color:                   | Dark brown, laminated    |
| Compartment dimensions:  | 16 cm x 15 cm x 15,5 cm  |
| Inside dimensions:       | 33 cm x 31 cm x 15,5 cm  |
| Dimensions:              | Width: 37 cm             |
|                          | Depth: 35 cm             |
|                          | Height: 25,5 cm          |
| Weight:                  | 4,59 kg                  |
|                          |                          |