

EUROLITE Set 4x LED PAR-64 HCL 12x10W bk + Case

4 LED spots with matching PRO flightcase

Art. No.: 2000046

GTIN:



List price: 1426.81 €

incl. 19% VAT.

Features:

EUROLITE LED PAR-64 HCL 12x10W Floor bk

PAR spot with 12 x 10 W 6in1 LED in R, G, B, A, W, UV

- 12 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect; UV effect
- Control via stand-alone; DMX; Sound to light via Microphone; IR remote control
- With a beam angle of 33°
- With double bracket
- The device is cooled by temperature-controlled fan
- Preprogrammed in Light´J; LED PC-Control 512; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x6; Light Captain
- 3 integrated show programs
- Direct color selection for 15 preset colors
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Stage; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

ROADINGER Flightcase 4x PAR-64 Spot short

Trunk case, PRO version

- Detachable compartments - case can also be used as universal transport case

Logistic

- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 21,85 kg

EUROLITE LED PAR-64 HCL 12x10W Floor bk

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 125 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED: | 12 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix) |
| DMX channels: | 4; 10 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; DMX; Sound to light via Microphone; IR remote control |
| Preprogrammed in: | Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x6; Light Captain |
| Beam angle: | 33° |
| Beam angle (1/2 peak): | 33° |
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 29,6 cm Depth: 27,7 cm Height: 37,5 cm |
| Weight: | 2,80 kg |
| Noise classification: | Class 2 (slight noise) |
| Photobiological safety: | Risk Group 0 |

Remote control

Battery: 1 x Button cell 3.0 V CR2025 lithium manganese built-in

ROADINGER Flightcase 4x PAR-64 Spot short

| | |
|--------------------------|---|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Device compartment: | 23 cm x 23 cm x 32,5 cm |
| Inside dimensions: | 46 cm x 46 cm x 32,5 cm |
| Dimensions: | Width: 51 cm Depth: 51 cm Height: 41,5 cm |
| Weight: | 10,65 kg |
