

EUROLITE Set LED PFE-50 + Lens tube 26°

Handy stage spotlight including lens tube

Art. No.: 2000061

GTIN: 4026397584721



List price: 415.31 €

incl. 19% VAT.

Features:

EUROLITE LED PFE-50 3000K Profile Spot

Handy stage spotlight with 50 W COB LED in modular construction system, CRI >80

- Modular construction kit that can be customized to individual preferences
- 4 shutter blades
- Dimmer and strobe, master/slave functions adjustable via optional DMX interface
- 1 powerful LED 50 W COB (chip-on-board) warm white (WW)
- The device is cooled by cooling fan
- Control via on/off switch on device; Master/slave function
- Preprogrammed in LED PC-Control 512; Light Captain; Light J
- Flicker-free
- With a beam angle of 19°
- Very high color rendering index (CRI)
- With Mounting bracket
- Very quiet working noise
- Dimmable
- For application areas such as: Trade fair and shop fitting; Installation; theater; Rental
- Application possibility: Suspended; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x filter frame, 1 x gobo holder, 1 x terminating plug (power)

Logistic

EAN / GTIN: 4026397584721

Weight: 3,10 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.42 m

EUROLITE Lens Tube 26° for LED PFE-50

Lens tube for EUROLITE LED PFE-50 3000 K Profile Spot

- Lens tube available with a beam angle of 19°, 26°, 36° or 50°

- With a beam angle of 26°

Technical specifications:

Weight: 2,19 kg

EUROLITE LED PFE-50 3000K Profile Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	55 W
IP classification:	IP20
Power connection:	Mains input via 3-pin screw plug connector (M) IP power supply cord with safety plug (provided)
Power output:	1 x 3-pin screw plug connector (F) IP
Lamp type:	LED lamp
Lamp specification:	Dimmable
LED:	1 x 50 W COB (chip-on-board) warm white (WW)
Color temperature:	3000K
Cooling:	Cooling fan
Control:	On/off switch on device; Master/slave function
Preprogrammed in:	LED PC-Control 512; Light Captain; Light´J
Projection:	Flicker-free
Beam angle:	19°
Beam angle (1/2 peak):	19° (optional) 26° (optional) 36° (optional) 50° (optional)
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Warm white (WW) 1m: 0 lx, 3m: 1669 lx, 6m: 432 lx
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 30,5 cm Width: 13,4 cm Height: 23,8 cm
Weight:	1,97 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE Lens Tube 26° for LED PFE-50

Beam angle: 26°

Beam angle (1/2 peak):	26°
Weight:	220 g