



Features:

ALUTRUSS TRILOCK 6082-2000 3-way Cross Beam

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

ALUTRUSS TRILOCK 6082-2500 3-way Cross Beam

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

ALUTRUSS TRILOCK 6082-3000 3-way Cross Beam

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm

Logistic

- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

ALUTRUSS TRILOCK 6082AL-31 3-way Corner Λ right

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school

ALUTRUSS TRILOCK 6082AL-32 3-way Corner Λ left

3-point truss system

- Low weight
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; clubs/dancing school

ALUTRUSS TRILOCK Base Plate QTG-male

- Trusspipe: 50 mm
- Made in Europe

ALUTRUSS QUICK-LOCK Spare Pivot

QUICK-LOCK spare pivot

- Accessories for the robust truss system with QUICK-LOCK
- For use with TRI/QUAD/E-GL33/QL-ET34 system
- Trusspipe: 50 mm
- Made in Europe

ALUTRUSS QUICK-LOCK Spare Pin

QUICK-LOCK spare pin

- Accessories for the robust truss system with QUICK-LOCK
- For use with TRI/QUAD/E-GL33/QL-ET34 system
- Trusspipe: 50 mm
- Made in Europe

Technical specifications:

Weight: 122.32 kg

ALUTRUSS TRILOCK 6082-2000 3-way Cross Beam

Setup: Easy installation

Trusspipe: 50 mm x 2 mm

Welding technique: TIG-welding

Welding material: AlMg 5

Color: Alu colored

Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 200 cm Width: 29 cm Height: 25.70 cm
Weight:	8.20 kg

ALUTRUSS TRILOCK 6082-2500 3-way Cross Beam

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 250 cm Width: 29 cm Height: 25.70 cm
Weight:	9.80 kg

ALUTRUSS TRILOCK 6082-3000 3-way Cross Beam

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Welding technique:	TIG-welding
Welding material:	AlMg 5
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 300 cm Width: 29 cm Height: 25.70 cm
Weight:	10.7 kg

ALUTRUSS TRILOCK 6082AL-31 3-way Corner \wedge right

Setup:	Easy installation
Trusspipe:	50 mm x 2 mm
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 50 cm Width: 50 cm Height: 50 cm
Weight:	6.1 kg

ALUTRUSS TRILOCK 6082AL-32 3-way Corner \wedge left

Setup:	Easy installation
--------	-------------------

Trusspipe:	50 mm x 2 mm
Color:	Alu colored
Strut diameter x thickness:	16 x 2mm
Dimensions:	Length: 50 cm Width: 50 cm Height: 50 cm
Weight:	6.20 kg

ALUTRUSS TRILOCK Base Plate QTG-male

Trusspipe:	50 mm
Color:	Alu colored
Weight:	0.94 kg

ALUTRUSS QUICK-LOCK Spare Pivot

Trusspipe:	50 mm
Color:	Alu colored
Weight:	0.04 kg

ALUTRUSS QUICK-LOCK Spare Pin

Trusspipe:	50 mm
Color:	Alu colored
Weight:	0.004 kg

Scope of delivery:

4 x ALUTRUSS TRILOCK 6082-2000 3-way Cross Beam

1 x connection set

4 x ALUTRUSS TRILOCK 6082-2500 3-way Cross Beam

1 x connection set

2 x ALUTRUSS TRILOCK 6082-3000 3-way Cross Beam

1 x connection set

2 x ALUTRUSS TRILOCK 6082AL-31 3-way Corner Λ right

2 x connection set

2 x ALUTRUSS TRILOCK 6082AL-32 3-way Corner Λ left

2 x connection set