

## EUROLITE Set PAR-16 Spot bk + GU-10 230V COB 7W 6400K

PAR-16 housing with GU-10 socket including special lamp for show effect lighting

Art. No.: 20000105

GTIN:



### Features:

- Mini-spot for GU-10 lamp
- Color-filters attachable
- Control via plug and play
- For PAR 16
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- <p>OMNILUX GU-10 230V COB 7W 6400K
- <h2 class="featureSatz">Special lamp for show effect lighting</h2>Spare lamp for Eurolite PAR-16 spots: 50850340 EUROLITE PAR-16 Spot GU-10 silver, 50850350 EUROLITE PAR-16 Spot GU-10 black, 50850352 EUROLITE PAR-16 Spot GU-10 white
- Hot restrike
- For further information about this product, please refer to the Data Sheet under "Downloads"

### Logistic

### Technical specifications:

Weight: 0.32 kg

### EUROLITE PAR-16 Spot GU-10 black

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 0.75 mm <sup>2</sup> H05SS-F
Cable length:	Approx. 0.4 m
Base:	GU10
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-16
Housing color:	Black
Material:	Aluminum, 1 mm
Slot for spot length:	7.8 cm x 7.8 cm
Dimensions:	Length: 17 cm Width: 11 cm Height: 13 cm
Weight:	0.28 kg
Noise classification:	Class 0 (no noise at all)
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Shape:	Octagonal
Material:	Aluminum, 1 mm
Dimensions:	Width: 7.7 cm Height: 7.7 cm Diameter: Ø 5.2 cm
Weight:	0.01 kg

#### **OMNILUX GU-10 230V COB 7W 6400K**

Voltage (lamps):	230 V, AC
Nominal wattage:	7 W
Base:	GU10
Lamp type:	LED lamp; clear lamp; high voltage lamp
Lamp specification:	Hot restrike
Beam angle:	90°
Color of light:	White
Color temperature:	6400K
Lead time:	1 s
Construction:	Reflector; bi pin
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	30000 h
Luminous flux:	550 lm

Lamp current:	0.06 A
Dimensions (LxD):	72x51 mm
Weight:	0.04 kg
Energy efficiency class (A++ - E):	A+

---

**Scope of delivery:**

---

1 x spotlight  
1 x filter frame  
1 x user manual