



The article is no longer in our assortment.

Features:

EUROLITE DF-40 LED display 92x92

Ultra flat and flexible LED display

- Ultraflat and flexible LED display for bright and colorful projection of videos and graphics
- Bends, rolls and moulds around almost any shape for waves, columns, circles, arcs and angles
- 4 millimeters thin and 800 grams light for convenient transport and simple installation
- 40 mm pixel pitch (seamless image at about 40 m)
- Applicable for installation in counters, columns and rear walls in shops and clubs, on fairs and various other environments
- Extendable for of large video billboards
- Control per network protocol in live mode with PC software or in stand-alone mode with media player (accessories)
- Control also possible per MADRIX, DMX and Artnet
- Large operating range from -20° to +50° C
- 484 powerful LEDs SMD 3in1 TCL RGB (homogenous color mix)
- Control via DMX

EUROLITE DF Control system

Control unit for DF-40 LED display

- Control unit and PC software for controlling DF-40 LED displays
- Operation with the handy media player (80503610) or a network-compatible computer
- Create stunning light shows for your displays with the included light effect software
- Load your shows onto the included SD memory card for playback on the media player
- Ethernet input and output, LAN cable included

Logistic

EUROLITE DF power unit

Mountable power unit for DF-40 LED displays

- Power unit in aluminum housing for DF-40 LED displays
- Each DF-40 LED display requires a separate power unit
- Screw terminals
- Short-circuit proof, overload-protected
- Protected against excess temperature

Technical specifications:

Weight: 5,60 kg

EUROLITE DF-40 LED display 92x92

Power consumption: 40,00 W

LED: 484 x SMD 3in1 TCL RGB (homogenous color mix)

Control: DMX

Dimensions: Width: 92,5 cm
Depth: 4 cm
Height: 92 cm

Weight: 600 g

Resolution: 22 x 22 pixels

Pixel pitch: 40 mm

Pixel configuration: tricolor RGB LEDs

Display mode: synchronous to PC, or asynchronous per media player

Brightness: R 250-1000 mcd, G 500-1650 mcd, B 80-500 mcd

Viewing angle: 120°

Data refresh rate: 400 cycles/sec

Colors: 16.7 million (R 256, G 256, B 256)

Operating temperature: -20° to 50°C

Dimensions (L x W x H): 925 x 920 x 4 mm

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

EUROLITE DF Control system

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 10,00 W

Dimensions: Width: 16 cm
Depth: 15,5 cm
Height: 5 cm

Weight:	1,10 kg
Signal input:	RJ45, CAT5e
Signal link:	RJ45, CAT5e
Number of displays:	max. 6 per control unit
Serial connection:	max. 255 control units for PC operation max. 48 control units for media player operation
Pixels:	max. 3072
Dimensions (L x W x H):	160 x 155 x 50 mm
System requirements:	Windows XP, Vista or 7 Separate network card (100 Mbps) SD card reader

EUROLITE DF power unit

Power supply:	100-240 V AC, 50/60 Hz
Dimensions:	Width: 23 cm Depth: 15,5 cm Height: 5 cm
Weight:	900 g
Output voltage:	5 V DC
Output current:	40 A
Dimensions (L x W x H):	230 x 155 x 50 mm