

## EUROLITE Set 2x LED THA-40PC bk + Case

2x fanless Pc spot including PRO flightcase

Art. No.: 20000164

GTIN:



**List price: 1034.11 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED THA-40PC Theater Spot bk

Fanless PC spot (DMX), warm white 57 W LED, color rendering index (CRI) >90

- 1 powerful LED 57 W COB (chip-on-board) warm white (WW)
- Dimmer electronic; dimmer curves with adjustable response; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX
- Preprogrammed in LED PC-Control 512; Light´J; Light Captain; Colorchief
- Flicker-free
- With a beam angle of 11° - 48°
- Very high color rendering index (CRI)
- With mounting bracket
- LCD display
- Rubber feet
- Silent operation
- For application areas such as: Trade fair and shop fitting; installation; stage; theater
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x barn door, 1 x filter frame, 1 x user manual

### Logistic

#### ROADINGER Flightcase 2x THA-40 PC

Trunk case, PRO version

- With accessory compartment

- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

Weight:	15,85 kg
---------	----------

### EUROLITE LED THA-40PC Theater Spot bk

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	40 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Fuse:	5 x 20 mm, T 1 A fuse replaceable
LED type:	1 x 57 W COB (chip-on-board) warm white (WW)
DMX channels:	1; 2
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX
Preprogrammed in:	LED PC-Control 512; Light´J; Light Captain; Colorchief
Projection:	Flicker-free
Beam angle:	11° - 48°
Beam angle (1/2 peak):	11 - 37°
Beam angle (1/10 peak):	17 - 48°
Color temperature:	3100K
Color rendering index (CRI):	91 Ra
Illuminance in Lux (lx):	Narrow 3m: 1656 lx, 6m: 424 lx Wide 3m: 348 lx, 6m: 103 lx
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Transport aid:	Rubber feet
Material:	Aluminum casting
Slot for spot length:	13,1 cm x 13,1 cm
Dimensions:	Length: 27,5 cm

	Width: 20,5 cm Depth: 25 cm
Weight:	3,85 kg
Noise classification:	Class 0 (no noise at all)
Mounting bracket	
Diameter mounting holes:	1 x Ø10mm; 2 x Ø6mm
Material:	Metal, 3 mm
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1 m
Barndoor	
Material:	Aluminum, 1,5 mm; metal
Ring diameter:	Outside: 12,9 mm Inside: 10,9 mm
Filter frame	
Diameter mounting holes:	1 x Ø4mm
Shape:	Octagonal
Material:	Aluminum, 0,8 mm
Dimensions:	Width: 13 cm Height: 13 cm Diameter: Ø 10,5 cm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 2x THA-40 PC**

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	16 cm x 31 cm x 12 cm
Accessory compartment:	10,5 cm x 31 cm x 18 cm
Inside dimensions:	60 cm x 31 cm x 20 cm
Dimensions:	Width: 64,5 cm Depth: 35 cm Height: 29 cm
Weight:	8,15 kg