



Features:

EUROLITE LED KLS-200 Compact-Light-Set

Bar with 4 spots with 108 LEDs (RGB) each and carrying bag

- Complete LED light set with four slimline LED spots
- Crossbar with integrated DMX control unit
- Installation via TV pin for tripods with 28 mm interior diameter
- Ultra-light ideally suited for mobile use
- Comes pre-assembled with practical transport bag
- 108 x 10 mm LED per spot (36 x red, 36 x green, 36 x blue)
- Movable and tiltable spotlights
- DMX-controlled operation or stand-alone operation with processor-controlled color change
- Master/Slave operation
- Sound-control via built-in microphone with sensitivity control
- Convenient control possible via optional 4-pedal foot pedal FP-1 (preset, sound control, freeze, blackout)
- DMX512 control via regular DMX controller (occupies 15 channels)
- Optimized for control with the optional control panel DMX LED Operator 4
- Via DMX, each spot can be individually controlled
- DMX functions: dimmer, automatic mode, music control, strobe effect
- Addressing and setting via control panel with 4-digit LED display
- Suited for installation on a lighting stand (not included)
- Ideal for bands, stages or solo entertainers
- Ready for connection with power cord and safety plug
- 432 LEDs 10 mm R/G/B
 spots controlled separately
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; foot switch (optional)
- With a beam angle of 25°

Logistic

- For further information about this product, please refer to the Data Sheet under "Downloads"

ROADINGER Flightcase KLS Compact Light Sets

PRO flightcase with telescopic handle for 1 x KLS compact light set

- Professional transport solution with extendable trolley for EUROLITE KLS compact light sets
- Suitable for KLS-200, KLS-300, KLS-400, KLS-401, KLS-800, KLS-801, KLS-1001 and KLS-2001
- Compartments for 1 KLS Compact Light Set, 1 foot controller and further accessories
- High-quality workmanship with multiplex birch wood, dark brown laminated
- Aluminum profile frames (30 mm) with rounded edges
- Interior upholstered with foam
- Three-leg, medium-sized steel ball corners
- 3 hinges
- 2 high-quality butterfly locks
- 3 case handles
- 2 castors
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Trolley
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	20.65 kg
---------	----------

EUROLITE LED KLS-200 Compact-Light-Set

Power supply:	230 V AC, 50 Hz
Power consumption:	55 W
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	432 x 10 mm R/G/B
DMX channels:	15
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; foot switch (optional)
Fixtures available for:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle (1/2 peak):	25°
Housing color:	Black
Weight:	8.65 kg
Dimensions:	Width: 120 cm Depth: 12 cm Height: 38 cm
DMX connection:	3-pin XLR
TV spigot:	D = 28 mm
Dimensions (L x W x H):	1110 x 55 x 295 mm
Special product:	Not designed for household room illumination

Intended use: Show effect lighting

ROADINGER Flightcase KLS Compact Light Sets

Maximum load:	50 kg
Transport aid:	Trolley
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	42 cm x 16.5 cm x 12 cm
Inside dimensions:	122.5 cm x 26 cm x 12 cm
Dimensions:	Width: 126.5 cm Depth: 37.5 cm Height: 22 cm
Weight:	12.00 kg

Scope of delivery:

- 1 x spotlight
- 1 x bag