

EUROLITE Set LED TSL-200 Scan COB + Case

Scanner with 20 W COB LED, rotating gobos and color wheel including flightcase

Art. No.: 20000216

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED TSL-200 Scan COB

Scanner with 20 W COB LED, rotating gobos and color wheel

- Equipped with a 20 W COB LED
- Long LED life
- Comparable to the light output of a 250 W halogen lamp
- DMX-controlled operation or stand-alone operation with Master/Slave function (up to 4 slaves)
- 14 motion macros can be called up via DMX controller
- Microphone-sensitivity adjustable via rotary-control
- Fuzzy sound control: program continues automatically during periods without music or bass-beat
- Strobe effect with 1-18 flashes per second
- Strobe effect with adjustable speed
- Random strobe effect
- Manual focus
- Dimmer
- Small and portable
- Lightbeam with 13° radiation angle
- Control board with 4-digit display for adjusting the DMX-starting address, Pan/Tilt-Reverse
- 6.3 mm jack socket for remote control
- Blackout, gobos, colors and Auto/Manual Mode applicable in Stand Alone mode via optional EUROLITE RC-1 remote control
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX control via any standard DMX controller
- 1 powerful LED 20 W COB (chip-on-board) cold white (CW)
- Focus manual

Logistic

- Gobo effect
- Color wheel with 7 dichroic filters plus open
Rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone; Sound to light via Microphone
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain
- With a beam angle of 13°
- 4 digit 7-segment LED display

Package contents

- 1 x light effect, 1 x user manual, 1 x power cord

ROADINGER Flightcase TSL-100/200

Trunk case, PRO version

- With 1 Device compartment
- High-quality workmanship with plywood multi-layer glued 6 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 22mm with rounded edges
- Hinged, chromium plated case handle
- 2 high-quality butterfly locks
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 11,50 kg

EUROLITE LED TSL-200 Scan COB

| | |
|--------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 70 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Lamp type: | LED lamp |
| LED: | 1 x 20 W COB (chip-on-board) cold white (CW) |
| Flash rate: | 0 - 18 Hz |
| Equipment: | Focus manual |
| Color generation: | Color wheel with 7 dichroic filters plus open Rainbow effect with adjustable speed in both directions |
| Gobos: | Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 25mm Image diameter 20mm Shake effect |
| DMX channels: | 9 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |

| | |
|------------------------|---|
| Cooling: | Cooling fan |
| Control: | DMX; stand-alone; Sound to light via Microphone |
| Preprogrammed in: | LED PC-Control 512; EASY SHOW 1; Light Captain |
| Beam angle: | 13° |
| Beam angle (1/2 peak): | 13° |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Width: 20,5 cm Depth: 39 cm Height: 30 cm |
| Weight: | 6,20 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase TSL-100/200

| | |
|--------------------------|---|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 22 mm |
| Case handle: | 1 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Plywood multi-layer glued, 6 mm |
| Color: | Black, laminated |
| Inside dimensions: | 37,5 cm x 21 cm x 17 cm |
| Device compartment: | 38,5 cm x 21,5 cm x 17 cm |
| Dimensions: | Width: 48 cm Depth: 25,5 cm Height: 27,5 cm |
| Weight: | 5,30 kg |