

EUROLITE Set LED TSL-200 Scan COB + Case

Scanner with 20 W COB LED, rotating gobos and color wheel including flightcase

Art. No.: 20000216

GTIN:



Features:

- Equipped with a 20 W COB LED
- Long LED life
- Comparable to the light output of a 250 W halogen lamp
- DMX-controlled operation or stand-alone operation with Master/Slave function (up to 4 slaves)
- 14 motion macros can be called up via DMX controller
- Microphone-sensitivity adjustable via rotary-control
- Fuzzy sound control: program continues automatically during periods without music or bass-beat
- Strobe effect with 1-18 flashes per second
- Strobe effect with adjustable speed
- Random strobe effect
- Manual focus
- Dimmer
- Small and portable
- Lightbeam with 13° radiation angle
- Control board with 4-digit display for adjusting the DMX-starting address, Pan/Tilt-Reverse
- 6.3 mm jack socket for remote control
- Blackout, gobos, colors and Auto/Manual Mode applicable in Stand Alone mode via optional EUROLITE RC-1 remote control
- Advantages of LED technology: long life, low power consumption, minimal heat emission, defacto maintenance free with brilliant light radiation
- DMX control via any standard DMX controller
- 1 LED 20 W COB (chip-on-board) cold white (CW)
- Focus manual
- Gobo effect

Logistic

- Color wheel with 7 dichroic filters plus open
rainbow effect with adjustable speed in both directions
- Gobo wheel with rotating gobos, 7 gobos and open
shake effect
- The device is cooled by cooling fan
- Control via DMX; stand-alone; sound to light via microphone
- With a beam angle of 13°
- 4 digit 7-segment LED display
- <p>ROADINGER Flightcase TSL-100/200
- <h2 class="featureSatz">Trunk case, PRO version</h2>With 1 device compartment
- High-quality workmanship with plywood multi-layer glued 6 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 22mm with rounded edges
- Hinged, chromium plated case handle
- 2 high-quality butterfly locks
- Branded hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight:	11.50 kg
---------	----------

EUROLITE LED TSL-200 Scan COB

Power supply:	230 V AC, 50 Hz
Power consumption:	70 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 20 W COB (chip-on-board) cold white (CW)
Flash rate:	0 - 18 Hz
Equipment:	Focus manual
Color generation:	Color wheel with 7 dichroic filters plus open Rainbow effect with adjustable speed in both directions
Gobos:	Gobo wheel with rotating gobos, 7 gobos and open Outside diameter 25mm Image diameter 20mm Shake effect
DMX channels:	9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	DMX; stand-alone; sound to light via microphone
Fixtures available for:	LED PC-Control 512; EASY SHOW 1; Light Captain
Beam angle (1/2 peak):	13°
Housing color:	Black

Display type:	4 digit 7-segment LED display
Dimensions:	Width: 20.5 cm Depth: 39 cm Height: 30 cm
Weight:	6.20 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase TSL-100/200

Maximum load:	25 kg
Aluminum profile frames:	22 mm
Case handle:	1 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Plywood multi-layer glued, 6 mm
Color:	Black, laminated
Inside dimensions:	37.5 cm x 21 cm x 17 cm
Device compartment:	38.5 cm x 21.5 cm x 17 cm
Dimensions:	Width: 48 cm Depth: 25.5 cm Height: 27.5 cm
Weight:	5.30 kg

Scope of delivery:

- 1 x light effect
- 1 x user manual
- 1 x power cord