

## OMNITRONIC Set 2x ARM-6.5 studio monitor + 2x MO-1 stand

2x active 2-way reference studio monitor including 2 monitor stands

Art. No.: 2000234

GTIN: 4026397593556



**The article is no longer in our assortment.**

### Features:

#### OMNITRONIC MO-1 Monitor Stand

Monitor stand, extendible from 93-148 cm, maximum load 18 kg

- Particularly suited for near-field monitors
- Auto-lock safety pin
- Solid metal version
- Adjustable height

#### OMNITRONIC ARM-6.5 2-Way Studio Monitor

Active 2-way reference studio monitor with ribbon transducer and Kevlar woofer

- 2-way active speaker system for studio and multimedia applications
- Crystal clear and precise listening experience through built-in 5 cm velocity ribbon tweeter (2") with wave guide
- 16.5 cm bass-midrange speaker (6.5") with Kevlar cone delivers rich and defined lows
- Separate power amplifiers for bass speaker and tweeter (bi-amping) with efficient class AB circuitry, ensuring serious dynamic headroom
- Low weight due to integrated switch mode power supply
- Extensive controls for adjustment to various acoustic conditions
- Click type rotary volume control at front for precise level adjustment
- Equipped with an unbalanced RCA input and a balanced XLR input and a 6.3 mm jack input
- High-quality MDF cabinet (15 mm) with front acoustic port and optimized internal bracing
- Black high-gloss surface

### Logistic

EAN / GTIN: 4026397593556

Weight: 23,40 kg

Length: 0.95 m

Width: 0.80 m

Height: 0.76 m

Bulky product

## Technical specifications:

---

Weight: 21,76 kg

---

### OMNITRONIC MO-1 Monitor Stand

Maximum carrying capacity: 18 kg

---

Height: Maximum: 148 cm  
Minimum: 93 cm

---

Attachment system: 4 holes

---

Type (general stands): Speaker stand/manual

---

Material: Steel

---

Color: Black

---

Base area: 40 cm x 40 cm

---

Storage area: 20 cm x 22 cm

---

Weight: 3,73 kg

---

### OMNITRONIC ARM-6.5 2-Way Studio Monitor

Power supply: 100-240 V AC, 50/60 Hz

---

Power consumption: 42 W

---

Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

---

Power: Program: 120W LF  
Rated: 60W RMS LF  
Program: 40W HF  
Rated: 20W RMS HF

---

Frequency range: 45 - 22000 Hz

---

S/N ratio: >95 dB

---

Max. SPL: 102 dB

---

Impedance: 4/8 ohms biamp

---

Impedance: Input: 10 kOhm , bal.  
Input: 20 kOhm , unbal.

---

Room compensation: 0 dB, -2 dB, -4 dB; switchable

---

HF adjustment: -2 dB, 0 dB, 2 dB; switchable

---

Low cut: FLAT, 80Hz, 100Hz, switchable

---

Circuitry: Class AB Biamp

---

Controls: Overheat; current limiting; power on/off transient; subsonic filter

---

Status LED: Power, Standby

---

Connections: Input: line via 1 x RCA (F) mounting version  
Input: line via 1 x 6.3 mm jack socket (mono) mounting version

	Input: line via 1 x 3-pin XLR
Crossover frequency:	2800 Hz
Input sensitivity:	85 mV
Speaker:	1 x woofer 6,5" Conematerial: Kevlar 1 x ribbon tweeter 2" With wave guide
Type of speaker:	Monitor for studios
Dimensions:	Width: 23 cm Depth: 27,5 cm Height: 35,8 cm
Weight:	7,15 kg