

EUROLITE Set 4x AKKU UP-1 + SB-4 Soft Bag + QuickDMX Wireless Transmitter

4x LED uplight with black soft bag and wireless DMX transmitter

Article: 20000267

GTIN:



List price: 1248.31 €

incl. 19% VAT.

Features:

EUROLITE AKKU UP-1 QCL Flex Spot QuickDMX

LED uplight with 15 W 4in1 LED, tiltable head and QuickDMX transceiver

- Integrated QuickDMX transceiver for wireless DMX control
- Inclination angle of the LED head manually adjustable
- Interchangeable front lens for 9° or 15° beam angle
- Cordless, flexible and versatile
- Battery operation up to 18h depending on program used
- Integrated automatic charging of the battery and status indicator
- 1 powerful LED 15 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; colors preset; color blend stepless; color change adjustable; Dimmer electronic
- Strobe effect
- The device is cooled by passive convection cooling
- Control via DMX; stand-alone; QuickDMX; sound to light via microphone; IR remote control
- Preprogrammed in Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 9°
- For application areas such as: Mobile djs / entertainer; wedding/gala/events; mobile use; small rental
- Silent operation
- Application possibility: Standing

Package contents

- 1 x spotlight, 1 x external mains adapter, 1 x remote control, 2 x battery, 1 x lens, 1 x omega bracket, 1 x user manual, 1 x power cord

Logistic

EUROLITE SB-4 Soft Bag L

Black soft bag for up to 4 devices, 320 x 320 x 200 mm

- Practical transport bag offers enough space for several lighting effects and accessories
- With dividers
- With 2 Outside pockets
- With 4 device compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
cover with foam padding
- 2 carrying straps

Package contents

- 1 x bag

EUROLITE QuickDMX Wireless Transmitter

Compact wireless DMX transmitter 2.4 GHz

- User-friendly 3-pin XLR adapter (male) with swivel antenna
- Wireless DMX eliminates extensive cabling between DMX controller and the DMX-controlled units in lighting installations
- Due to GFSK modulation with 78 channels, interference-free operation also alongside other QuickDMX transceiver and wireless devices in the 2.4 GHz band (e.g. Wi-Fi and Bluetooth)
- 1 to 512 QuickDMX receivers can be controlled by each transmitter
- LED indication for functions
- Transceiver, to be used as transmitter or receiver
- Can transmit up to 512 DMX channels
- Control via QuickDMX; DMX; plug and play
- Operating range up to 400m
- Up to 6 transmitters can be operated in parallel without interference

Package contents

- 1 x device, 1 x user manual, 1 x declaration of conformity, 1 x external mains adapter, 1 x USB cable

Technical specifications:

Weight:	9,51 kg
---------	---------

EUROLITE AKKU UP-1 QCL Flex Spot QuickDMX

Power consumption:	15 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Battery pack type:	1 x lithium ion 7,4 V, 8800 mAh, 65,12 Wh
Battery pack:	Battery operation up to 18h depending on program used Recharging time 6h
Lamp type:	LED lamp
LED type:	1 x 15 W SMD 9080 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10

DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	DMX; stand-alone; QuickDMX; sound to light via microphone; IR remote control
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	9°
Beam angle (1/2 peak):	9° 15°
Beam angle (1/10 peak):	18° 30°
Housing color:	Black
Dimensions:	Width: 12 cm Depth: 12 cm Height: 14,2 cm
Weight:	2,21 kg
Noise classification:	Class 0 (no noise at all)
External mains adapter	
Power supply:	100-240 V AC, 50/60 Hz 8,4V 3000 mA
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE SB-4 Soft Bag L

Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon
Color:	Black, water repellent
Compartment dimensions:	15 cm x 15 cm x 20 cm
Inside dimensions:	31 cm x 34 cm x 20 cm
Dimensions:	Width: 32 cm Depth: 41 cm Height: 20 cm
Weight:	0,52 kg

EUROLITE QuickDMX Wireless Transmitter

Power supply:	100-240 V AC, 50/60 Hz
---------------	------------------------

	5V DC 1000 mA
IP classification:	IP20
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord for USB A mains connection (provided)
DMX channels:	Output 512
DMX input:	1 x 3-pin XLR (M)
Control:	QuickDMX; DMX; plug and play
Range:	Range up to 400m
Carrier frequency:	2,4 GHz
Parallel mode:	Max. 6 transmitter
RF power output:	19 dBm
Modulation:	GFSK
Color:	Silver
Dimensions:	Length: 21,2 cm Diameter: Ø 1,8 cm
Weight:	0,15 kg