

## EUROLITE Set PAR-30 Spot bk + PAR-30 230V SMD 11W E-27 LED 3000K Art. No.: 20000284

PAR-30 housing with E-27 socket including PAR-30 lamp with LED technology

GTIN:



**List price: 35.58 €**

incl. 19% VAT.

### Features:

#### EUROLITE PAR-30 Spot black

PAR-30 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With mounting bracket
- For PAR 30
- For application areas such as: Advertisement/Shop window; decoration; clubs/dancing school

#### Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

### Logistic

#### OMNILUX PAR-30 230V SMD 11W E-27 LED 3000K

PAR-30 LED lamp

- Easy lamp replacement
- Energy-saving
- Easy installation
- Good color rendering index (CRI)

## Technical specifications:

---

|         |         |
|---------|---------|
| Weight: | 0,72 kg |
|---------|---------|

---

### EUROLITE PAR-30 Spot black

|                          |   |
|--------------------------|---|
| Power supply:            | 230 V AC, 50 Hz   |
| Power consumption:       | Max. 100 W  |
| IP classification:       | IP20  |
| Protection class:        | Protection class I                                      |
| Suitable lamp:           | Max. 230 V/100 W E27                                    |
| Power connection:        | Fixed power supply cord with safety plug                |
| Cable construction:      | 3 x 0,75 mm² H05SS-F                                    |
| Cable length:            | Approx. 0,4 m   |
| Base:                    | E27   |
| Lamp type:               | Selectable  |
| Color generation:        | Via color filter frame                                  |
| Control:                 | Plug and play   |
| Construction:            | PAR-30  |
| Housing color:           | Black matte   |
| Attachment system:       | Mounting bracket  |
| Material:                | Aluminum  |
| Slot for spot length:    | 12,8 cm x 12,8 cm                                       |
| Dimensions:              | Length: 23,5 cm<br>Width: 14,5 cm<br>Height: 21 cm      |
| Weight:                  | 0,53 kg   |
| Mounting bracket         |   |
| Diameter mounting holes: | 2 x Ø10mm   |
| Material:                | Aluminum, 3 mm  |
| Color:                   | Black, matte  |
| Filter frame             |   |
| Shape:                   | Octagonal   |
| Material:                | Aluminum, 0,5 mm  |
| Color:                   | Black, matte  |
| Dimensions:              | Length: 12,6 cm<br>Width: 12,6 cm<br>Diameter: Ø 9,4 cm |
| Weight:                  | 0,022 kg  |

### OMNILUX PAR-30 230V SMD 11W E-27 LED 3000K

|                                  |                          |
|----------------------------------|--------------------------|
| Voltage (lamps):                 | 230 V, AC                |
| Nominal wattage:                 | 11 W                     |
| Base:                            | E27                      |
| Lamp type:                       | LED lamp; reflector lamp |
| Beam angle:                      | 50°                      |
| Setup:                           | Easy installation        |
| Color of light:                  | White                    |
| Color temperature:               | 3000K                    |
| Color rendering index (CRI):     | 82 Ra                    |
| Lead time:                       | 0,2 s                    |
| Construction:                    | PAR-30                   |
| Operating temperature max.:      | 40° C                    |
| Operating temperature min.:      | 20° C                    |
| Burning position:                | S180 (universal)         |
| Lamp life:                       | 20000 h                  |
| Luminous flux:                   | 850 lm                   |
| Wavelength:                      | 605 nm                   |
| Lamp current:                    | 0,086 A                  |
| Dimensions (LxD):                | 92x95 mm                 |
| Weight:                          | 0,19 kg                  |
| Energy efficiency class (A - G): | F                        |
| EPREL-Nr:                        | 979334                   |