

EUROLITE Set PAR-30 Spot sil + PAR-30 230V SMD 11W E-27 LED 3000K Art. No.: 20000285

PAR-30 housing with E-27 socket including PAR-30 lamp with LED technology

GTIN:



List price: 35.58 €

incl. 19% VAT.

Features:

EUROLITE PAR-30 Spot silver

PAR-30 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With mounting bracket
- For PAR 30
- For application areas such as: Advertisement/Shop window; decoration; clubs/dancing school

Package contents

- 1 x spotlight, 1 x filter frame, 1 x user manual

Logistic

OMNILUX PAR-30 230V SMD 11W E-27 LED 3000K

PAR-30 LED lamp

- Easy lamp replacement
- Energy-saving
- Easy installation
- Good color rendering index (CRI)

Technical specifications:

Weight:	0,66 kg
---------	---------

EUROLITE PAR-30 Spot silver

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 100 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0,4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-30
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	12,8 cm x 12,8 cm
Dimensions:	Length: 23,5 cm Width: 14,5 cm Height: 21 cm
Weight:	0,47 kg
Mounting bracket	
Material:	Aluminum
Filter frame	
Material:	Aluminum
Dimensions:	Length: 12,6 cm Width: 12,6 cm Diameter: Ø 9,4 cm
Weight:	0,018 kg

OMNILUX PAR-30 230V SMD 11W E-27 LED 3000K

Voltage (lamps):	230 V, AC
Nominal wattage:	11 W
Base:	E27
Lamp type:	LED lamp; reflector lamp
Beam angle:	50°
Setup:	Easy installation

Color of light:	White
Color temperature:	3000K
Color rendering index (CRI):	82 Ra
Lead time:	0,2 s
Construction:	PAR-30
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	20000 h
Luminous flux:	850 lm
Wavelength:	605 nm
Lamp current:	0,086 A
Dimensions (LxD):	92x95 mm
Weight:	0,19 kg
Energy efficiency class (A - G):	F
EPREL-Nr:	979334