



Features:

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Suitable for different spot angles
- Small lighting-systems can also be realized with a small budget
- Control via plug and play
- With mounting bracket
- For PAR 30
- For application areas such as: Clubs/dancing school; decoration; Trade fair and shop fitting; party room; restaurants, bars and hotels; advertisement/Shop window
- Silent operation
- <p>OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K
- <h2 class="featureSatz">PAR-30 LED lamp</h2>Easy lamp replacement
- Energy-saving
- Hot restrike
- Easy installation
- Good color rendering index (CRI)

Logistic

EAN / GTIN: 4026397472158
Weight: 0,80 kg
Length: 0.30 m
Width: 0.22 m
Heigth: 0.21 m

Technical specifications:

Weight: 0.70 kg

Energy efficiency class (A - G): F

EUROLITE PAR-30 Spot silver

| | |
|-----------------------|---|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | Max. 100 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Fixed power supply cord with safety plug |
| Cable length: | Approx. 0.4 m |
| Base: | E27 |
| Lamp type: | Selectable |
| Color generation: | Via color filter frame |
| Control: | Plug and play |
| Construction: | PAR-30 |
| Housing color: | Silver |
| Attachment system: | Mounting bracket |
| Material: | Aluminum |
| Slot for spot length: | 12.8 cm x 12.8 cm |
| Dimensions: | Length: 23.5 cm Width: 14.5 cm Height: 21 cm |
| Weight: | 0.47 kg |
| Noise classification: | Class 0 (no noise at all) |
| Material: | Aluminum |
| Material: | Aluminum |
| Dimensions: | Length: 12.6 cm Width: 12.6 cm Diameter: Ø 9.4 cm |
| Weight: | 0.018 kg |

OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K

| | |
|------------------------------|-------------------|
| Voltage (lamps): | 230 V, AC |
| Nominal wattage: | 11 W |
| Base: | E27 |
| Lamp type: | LED lamp |
| Lamp specification: | Hot restrike |
| Beam angle: | 50° |
| Setup: | Easy installation |
| Color of light: | White |
| Color temperature: | 6500K |
| Color rendering index (CRI): | 83 Ra |
| Lead time: | 0.2 s |
| Construction: | PAR-30 |

| | |
|----------------------------------|------------------|
| Operating temperature max.: | 40° C |
| Operating temperature min.: | 20° C |
| Burning position: | S180 (universal) |
| Lamp life: | 20000 h |
| Luminous flux: | 850 lm |
| Wavelength: | 600 nm |
| Lamp current: | 0.087 A |
| Dimensions (LxD): | 92x95 mm |
| Weight: | 0.19 kg |
| Energy efficiency class (A - G): | F |
| EPREL-Nr: | 1016879 |

Scope of delivery:

1 x EUROLITE PAR-30 Spot silver

- 1 x spotlight
- 1 x filter frame
- 1 x user manual

1 x OMNILUX PAR-30 230V SMD 11W E-27 LED 6500K

- 1 x illuminant