



List price: 26.78 €

incl. 19% VAT.

Features:

EUROLITE PAR-20 Spot silver

PAR-20 housing with E27 socket (with plug + cable)

- 4 clip-to-hold clamps with spring locks for comfortable opening of the color filter frame
- Strong clamps with extension springs for safe hold and for quick opening of the rear housing cover
- Blackened tube for precise light output
- Strong cable tension relief
- Control via plug and play
- With Mounting bracket
- Available in various colors
- For PAR 20
- For application areas such as: Advertisement/Shop window; Decoration; Clubs/dancing school

Package contents

- 1 x spotlight, 1 x mounting bracket, 1 x filter frame, 1 x user manual

Logistic

OMNILUX PAR-20 230V SMD 6W E-27 LED 6500K

PAR-20 lamp

- Stronger with the same power consumption
- Better brightness and color of light thanks to SMD LED
- Hot restrike
- Good color rendering index (CRI)
- For application areas such as: Clubs/dancing school; Stage

Technical specifications:

Weight:	420 g
Energy efficiency class (A - G):	F

EUROLITE PAR-20 Spot silver

Power supply:	230 V AC, 50 Hz
Power consumption:	Max. 75 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable length:	Approx. 0,4 m
Base:	E27
Lamp type:	Selectable
Color generation:	Via color filter frame
Control:	Plug and play
Construction:	PAR-20
Housing color:	Silver
Attachment system:	Mounting bracket
Material:	Aluminum
Slot for spot length:	8,5 cm x 8,5 cm
Dimensions:	Width: 15 cm Depth: 18 cm Height: 11,2 cm Diameter: Ø 8 cm
Weight:	320 g
Mounting bracket	
Diameter mounting holes:	2 x Ø10mm
Material:	Aluminum, 3 mm
Filter frame	
Material:	Aluminum
Dimensions:	Length: 8,4 cm Width: 8,4 cm Diameter: Ø 6,1 cm

OMNILUX PAR-20 230V SMD 6W E-27 LED 6500K

Voltage (lamps):	230 V
Nominal wattage:	6 W
Base:	E27
Lamp type:	LED lamp; clear lamp; high voltage lamp
Lamp specification:	Hot restrike

Beam angle:	50°
Color of light:	White
Color temperature:	6500K
Color rendering index (CRI):	81 Ra
Lead time:	0,2 s
Construction:	PAR-20
Operating temperature max.:	40° C
Operating temperature min.:	20° C
Burning position:	S180 (universal)
Lamp life:	20000 h
Luminous flux:	510 lm
Wavelength:	662 nm
Dimensions (LxD):	86x64 mm
Weight:	100 g
Photobiological safety:	Risk Group 0
Energy efficiency class (A - G):	F