



The article is no longer in our assortment.

Features:**OMNITRONIC DD-2550 USB Turntable sil**

Direct drive DJ turntable with switchable phono/line output and USB interface

- Built-in USB port and additional phono preamplifier, for a high-quality and convenient digitization of analog vinyl records
- Driver installation not required, unit is identified automatically
- Sampling rates of 44.1 kHz and 48 kHz in stereo, resolution: 16 bits
- Incl. software for recording and editing
- Precision direct drive
- Delivery includes pick-up system
- 2 speeds, pitch control $\pm 10\%$
- Large start/stop button
- Strobe lamp for exact speed adjustment
- Target lamp
- Delivery includes removable dustcover
- Adjustable anti-skating
- Shock-absorbing feet
- Switchable output phono/line
- USB 1.1 support
- Suitable for Windows XP, Vista, 7 and Mac OS X
- Pitch range: $\pm 10\%$
- The device can be connected via USB to the PC

Package contents

- 1 x turntable platter

Logistic

ROADINGER Turntable Case black -S-

Carrying case

- Suitable for all turntables without dust cover (up to 450 mm width)
- High-quality workmanship with plywood multi-layer glued 4 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Removable cover
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 2 high-quality spring locks
- Rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 15,50 kg

OMNITRONIC DD-2550 USB Turntable sil

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 12,00 W

Power connection: Fixed power supply cord with Euro plug

Frequency range: 20 - 20000 Hz

Drive type: Direct drive
Brushless DC motor

Drive: Initial torque: 1 kg/cm
Start time: 1 sec.
Stop time: 1 sec.
Speed change time: <1s 1khz 5cm/sec

Wow and flutter: <0,15 % WRMS

Rumble: 55 dB DIN B

Speed: 33 RPM; 45 RPM

Tone arm: S-shape with Cardan"s suspension
Length: 230
Overhang: 16 mm
Stylus pressure: 0-4 g, adjustable

Output level: Phono 1,5-3,6 mV/ 1 kHz 5 cm/sec
Line 90-216 mV/ 1 kHz 5 cm/sec

Connections: Output: line/phono via stereo RCA
Output: USB B (F) mounting version

Pitch range: $\pm 10\%$

USB port: USB 1.1, Typ B

Color: Silver

PC connect: Via USB

Dimensions: Width: 45 cm
Depth: 35 cm
Height: 15,5 cm

Weight: 11,30 kg

Turntable platter

| | |
|-------------|-------------------|
| Dimensions: | Diameter: Ø 33 cm |
|-------------|-------------------|

ROADINGER Turntable Case black -S-

| | |
|---------------|-------|
| Maximum load: | 15 kg |
|---------------|-------|

| | |
|-------------------|----------|
| Removable covers: | 1 pc/pcs |
|-------------------|----------|

| | |
|--------------------------|-------|
| Aluminum profile frames: | 25 mm |
|--------------------------|-------|

| | |
|------------------|----------|
| Carrying handle: | 1 pc/pcs |
|------------------|----------|

| | |
|-------|-----------------------|
| Lock: | Spring lock: 2 pc/pcs |
|-------|-----------------------|

| | |
|----------------|-------------|
| Transport aid: | Rubber feet |
|----------------|-------------|

| | |
|-----------|---------------------------------|
| Material: | Plywood multi-layer glued, 4 mm |
|-----------|---------------------------------|

| | |
|--------|------------------|
| Color: | Black, laminated |
|--------|------------------|

| | |
|---------------------|-------------------------|
| Device compartment: | 45 cm x 35,5 cm x 12 cm |
|---------------------|-------------------------|

| | |
|-------------|-----------------|
| Dimensions: | Width: 51,5 cm |
| | Depth: 46 cm |
| | Height: 21,5 cm |

| | |
|---------|---------|
| Weight: | 4,20 kg |
|---------|---------|
