

EUROLITE Set 4x LED SLS-603 + Case EC-SL4M size M

4x flat spotlight with 5 x 3 W 3in1 LED including practical flightcase

Art. No.: 2000306

GTIN: 4026397601183



Features:

- Slim design for space-saving applications
- DMX and power terminals intelligently designed for easy wiring
- 6 LEDs 3 W high-power 4in1 QCL RGB/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- UV effect; strobe effect
- Integrated show programs
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Fixtures available for Light'J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; Colorchief
- With a beam angle of 11°
- With double bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended; on stand
- For application areas such as: Clubs/dancing school; decoration; mobile djs / entertainer; party room; restaurants, bars and hotels
- <p>ROADINGER Flightcase EC-SL4M 4x SLS size M
- <h2 class="featureSatz">Trunk case</h2>With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, dark brown, laminated
- Interior with felt cover
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 1 high-quality butterfly lock

Logistic

EAN / GTIN: 4026397601183

Weight: 15,78 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.52 m

- Rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 14.04 kg

EUROLITE LED SLS-603 TCL + UV Floor

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 20 W

IP classification: IP20

Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

Power output: 1 x IEC connector (F) mounting version

Lamp type: LED lamp

LED type: 6 x 3 W high-power 4in1 QCL RGB/UV (homogenous color mix)

DMX channels: 4; 8

DMX input: 1 x 3-pin XLR (M) mounting version

DMX output: 1 x 3-pin XLR (F) mounting version

Cooling: 1 x cooling fan

Control: Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function

Fixtures available for: Light J; LED PC-Control 512; LED EASY OPERATOR DELUXE; Light Captain; Colorchief

Beam angle: 11°

Beam angle (1/2 peak): 11°

Beam angle (1/10 peak): 28°

Housing color: Black

Attachment system: Double bracket

Display type: 4 digit 7-segment LED display

Material: Plastic; metal; ABS Acrylonitrile butadiene styrene

Dimensions: Width: 23 cm
Depth: 11 cm
Height: 23 cm

Weight: 1.41 kg

Noise classification: Class 2 (slight noise)

Photobiological safety: Risk Group 0

Cable construction: 3 x 0.75 mm² H05VV-F

Cable length: Approx. 1.1 m

Diameter mounting holes: 5 x Ø11mm

Material: Metal, 2 mm

Color:	Black
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase EC-SL4M 4x SLS size M

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Transport aid:	Rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Dark brown, laminated; black, laminated
Compartment dimensions:	11.5 cm x 24.5 cm x 34 cm
Inside dimensions:	49 cm x 25 cm x 39 cm
Dimensions:	Width: 52.5 cm Depth: 28.5 cm Height: 44.5 cm
Weight:	8.40 kg

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual