

EUROLITE Set 4x LED SLS-180 + Case EC-SL4M size M

4x flat spotlight with 18 x 1 W LED including practical flightcase

Art. No.: 2000307

GTIN:



Features:

- Equipped with 18 x 1 W LED: 6 x red, 6 x green, 6 x blue
- Flat housing form requires minimal space when rigging
- Second mounting bracket for safe standing installation
- Additional rubber feet when the spot shall be positioned on the floor without mounting bracket
- Comfortable addressing and setting via control panel with LED display
- Functions: Static colors, three different color changes (2 x FC*, 1 x SC+) with adjustable speed, RGB color mixture, strobe effect, dimmer
- * FC = Fading Colors: uninterruptedly gradually fades out colors in a given period of time
- + SC = Switching Colors: uninterruptedly switches color in a given period of time
- Memory function
- Master/Slave for parallel operation of several devices
- IEC terminals for power linking up to 8 units
- Switch-mode power supply for operation between 100 and 240 volts
- 18 LEDs 1 W high-power R/G/B (homogenous color mix)
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone
- With a beam angle of 35°
- 4 digit 7-segment LED display
- <p>ROADINGER Flightcase EC-SL4M 4x SLS size M
- <h2 class="featureSatz">Trunk case</h2>With 4 device compartments
- High-quality workmanship with plywood multi-layer glued 7 mm, dark brown, laminated
- Interior with felt cover
- Aluminum profile frames 30mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks

Logistic

- 1 high-quality butterfly lock
- Rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 13.38 kg

EUROLITE LED SLS-180 RGB 18x1W Floor

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	12.00 W
Protection class:	Protection class II
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	1.4 m
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	18 x 1 W high-power R/G/B (homogenous color mix)
DMX channels:	3; 5; 7
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; sound to light via microphone
Fixtures available for:	Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
Beam angle (1/2 peak):	35°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 21 cm Depth: 10.5 cm Height: 22 cm
Weight:	1.25 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase EC-SL4M 4x SLS size M

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	1 pc/pcs

Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Transport aid:	Rubber feet
Material:	Plywood multi-layer glued, 7 mm
Color:	Dark brown, laminated; black, laminated
Compartment dimensions:	11.5 cm x 24.5 cm x 34 cm
Inside dimensions:	49 cm x 25 cm x 39 cm
Dimensions:	Width: 52.5 cm Depth: 28.5 cm Height: 44.5 cm
Weight:	8.40 kg

Scope of delivery:

1 x spotlight
1 x power cord
1 x user manual