



The article is no longer in our assortment.

Features:

EUROLITE AKKU TL-3 TCL Trusslight

Spotlight with 3 x 3 W 3in1 LED (RGB) for lighting within trussing

- Compact and bright, making it perfect for truss installation
- Cordless, flexible and versatile
- Equipped with 3 x 3 W TCL LED in red, green and blue
- Operation via mains connection or built-in rechargeable lithium-ion battery with up to 6.5 hours operating time
- Integrated automatic charging of the battery with indicator
- Controllable via EUROLITE IR-7 remote control; included in the delivery
- DMX-controlled operation or stand-alone operation with Master/Slave function
- 3, 5 or 8 DMX channels selectable
- Functions: static colors, stepless RGB color mixture, internal programs, dimmer, strobe effect with variable speed, sound-control, Master/Slave operation
- Dimmer speed (step response) adjustable
- Adjustable microphone sensitivity
- Addressing via control panel with 4-digit LED display
- Ideal for booth construction, stages and any kind of truss
- Ideal for ALUTRUSS 3-POINT SYSTEM DECOLOCK DQ3
- Hanging as well as standing installation possible
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included power cable with safety power plug
- Feed-through output allows to power up to 8 devices
- 3 powerful LEDs 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
- Control via DMX; stand-alone; sound to light via microphone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain
- Flicker-free

Logistic

- With a beam angle of 16°
device
- Cordless, flexible and versatile
- Battery operation up to 6,5h depending on program used
Package contents
- 1 x device, 1 x remote control

ROADINGER Flightcase 4x AKKU TL-3 Trusslight QuickDMX with charging function

Trunk case

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"
Package contents
- 1 x device, 1 x power cord, 1 x user manual

Technical specifications:

| | |
|---------|----------|
| Weight: | 14,50 kg |
|---------|----------|

EUROLITE AKKU TL-3 TCL Trusslight

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 19,00 W |
| IP classification: | IP20 |
| Power connection: | Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Lamp type: | LED lamp |
| LED type: | 3 x 3 W SMD 8072 3in1 TCL RGB (homogenous color mix) |
| Flash rate: | 0 - 30 Hz |
| DMX channels: | 3; 5; 8 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Control: | DMX; stand-alone; sound to light via microphone |
| Preprogrammed in: | Light J; LED PC-Control 512; Light Captain |
| Projection: | Flicker-free |
| Beam angle: | 16° |
| Beam angle (1/2 peak): | 16° |
| Beam angle (1/10 peak): | 34° |
| Housing color: | Black |

| | |
|--------------------|--|
| Dimensions: | Width: 12,1 cm Depth: 10,8 cm Height: 13,6 cm |
| Weight: | 1,35 kg |
| Battery pack type: | 1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh |
| Battery pack: | Battery operation up to 6,5h depending on program used Recharging time 4,5h |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x AKKU TL-3 Trusslight QuickDMX with charging function

| | |
|--------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | Max. 1150 W |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Device fuse: | 5 x 20 mm, T 5 A fuse replaceable |
| Aluminum profile frames: | 30 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs with shut-off function |
| Material: | Plywood multi-layer glued, 9 mm |
| Color: | Black, laminated |
| Compartment dimensions: | 15,5 cm x 15,5 cm x 11,5 cm |
| Accessory compartment: | 9 cm x 34 cm x 11,5 cm |
| Dimensions: | Width: 57 cm Depth: 37 cm Height: 24,5 cm |
| Weight: | 9,10 kg |