

## EUROLITE Set 4x LED PAR-56 QCL Short bk + EPS Case

4x PAR-56 Spot with 9 x 8 W 4in1 LED and RGBW color mixing including flightcase

Art. No.: 20000323

GTIN:



**List price: 831.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED PAR-56 QCL Short bk

PAR-56 spot with 9 x 8 W 4in1 LED and RGBW color mixing

- 9 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- Control via stand-alone; DMX; IR remote control; sound to light via microphone
- Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 8°
- With mounting bracket
- 4 digit 7-segment LED display
- Available in various colors
- For application areas such as: Clubs/dancing school; party room; stage; restaurants, bars and hotels
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

### Logistic

#### ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Trunk case

- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated

- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

|         |          |
|---------|----------|
| Weight: | 14,55 kg |
|---------|----------|

### EUROLITE LED PAR-56 QCL Short bk

|                         |                                                                                                                                                                        |
|-------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply:           | 100-240 V AC, 50/60 Hz                                                                                                                                                 |
| Power consumption:      | 50 W                                                                                                                                                                   |
| IP classification:      | IP20                                                                                                                                                                   |
| Power connection:       | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)                                                                       |
| Lamp type:              | LED lamp                                                                                                                                                               |
| LED type:               | 9 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)                                                                                                                |
| DMX channels:           | 4; 6; 8                                                                                                                                                                |
| DMX input:              | 3-pin XLR (M) mounting version                                                                                                                                         |
| DMX output:             | 3-pin XLR (F) mounting version                                                                                                                                         |
| Control:                | Stand-alone; DMX; IR remote control; sound to light via microphone                                                                                                     |
| Preprogrammed in:       | Light´ J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection:             | Flicker-free                                                                                                                                                           |
| Beam angle:             | 8°                                                                                                                                                                     |
| Beam angle (1/2 peak):  | 8°                                                                                                                                                                     |
| Beam angle (1/10 peak): | 25°                                                                                                                                                                    |
| Housing color:          | Black                                                                                                                                                                  |
| Attachment system:      | Mounting bracket                                                                                                                                                       |
| Display type:           | 4 digit 7-segment LED display                                                                                                                                          |
| Dimensions:             | Width: 20,5 cm<br>Depth: 17,5 cm<br>Height: 23 cm                                                                                                                      |
| Weight:                 | 1,65 kg                                                                                                                                                                |
| Photobiological safety: | Risk Group 0                                                                                                                                                           |
| Remote control          |                                                                                                                                                                        |
| Battery:                | 1 x button cell 3.0 V CR2025 lithium manganese built-in                                                                                                                |

### Legal specifications

|                  |                                              |
|------------------|----------------------------------------------|
| Special product: | Not designed for household room illumination |
| Intended use:    | Show effect lighting                         |

#### **ROADINGER Flightcase EPS-56 4x PAR-56 Spot short**

|                          |                                                   |
|--------------------------|---------------------------------------------------|
| Maximum load:            | 25 kg                                             |
| Aluminum profile frames: | 30 mm                                             |
| Case handle:             | 2 pc/pcs                                          |
| Stop hinge:              | 2 pc/pcs                                          |
| Lock:                    | Butterfly lock: 1 pc/pcs                          |
| Material:                | Birch multiplex, 7 mm                             |
| Color:                   | Dark brown, laminated                             |
| Compartment dimensions:  | 22 cm x 22 cm x 24 cm                             |
| Inside dimensions:       | 44 cm x 44 cm x 24 cm                             |
| Dimensions:              | Width: 48,5 cm<br>Depth: 48,5 cm<br>Height: 31 cm |
| Weight:                  | 7,95 kg                                           |