

EUROLITE Set 4x LED PAR-56 HCL Short sil + EPS Case

4x PAR-56 Spot with 9 x 10W 6in1 LED and RGBAW+UV color mixing including flightcase

Art. No.: 2000325

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED PAR-56 HCL Short sil

PAR-56 spot with 9 x 10 W 6in1 LED and RGBAW+UV color mixing

- Stepless color blend, color change, dimmer, strobe effect and UV effect
- 9 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Strobe effect; UV effect
- Control via stand-alone; DMX; Sound to light via Microphone; IR remote control
- Preprogrammed in Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x4; Light Captain
- Flicker-free
- With a beam angle of 20°
- With Mounting bracket
- 4 digit 7-segment LED display
- Available in various colors

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

Logistic

ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Trunk case

- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks

- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 15,10 kg

EUROLITE LED PAR-56 HCL Short sil

Power supply: 100-240 V AC, 50/60 Hz

Power consumption: 75 W

IP classification: IP20

Power connection: Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)

Lamp type: LED lamp

LED: 9 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)

DMX channels: 4; 6; 10

DMX input: 1 x 3-pin XLR (M) mounting version

DMX output: 1 x 3-pin XLR (F) mounting version

Control: Stand-alone; DMX; Sound to light via Microphone; IR remote control

Preprogrammed in: Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; LED EASY OPERATOR 4x4; Light Captain

Projection: Flicker-free

Beam angle: 20°

Beam angle (1/2 peak): 20°

Beam angle (1/10 peak): 38°

Housing color: Silver

Attachment system: Mounting bracket

Display type: 4 digit 7-segment LED display

Dimensions: Width: 20,5 cm
Depth: 17,5 cm
Height: 23 cm

Weight: 1,79 kg

Remote control

Battery: 1 x Button cell 3.0 V CR2025 lithium manganese built-in

Legal specifications

Special product: Not designed for household room illumination

Intended use: Show effect lighting

ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Maximum load:	25 kg
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	22 cm x 22 cm x 24 cm
Inside dimensions:	44 cm x 44 cm x 24 cm
Dimensions:	Width: 48,5 cm Depth: 48,5 cm Height: 31 cm
Weight:	7,95 kg