

EUROLITE Set 2x LED THA-100F Theater-Spot + Case

2x Fresnel spot, 100 W warm white LED, extremely quiet, DMX including PRO flightcase

Art. No.: 2000360

GTIN:



The article is no longer in our assortment.

Features:

EUROLITE LED THA-100F Theatre-Spot

Fresnel spotlight (fresnel lens), 100 W warm white LED, extremely quiet, DMX

- Light impression of a conventional 750 W lamp
- 1 powerful LED 100 W COB (chip-on-board) warm white (WW)
- Zoom manual
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via DMX
- Flicker-free
- With a beam angle of 10° - 60°
- With Mounting bracket
- LCD display
- Dimmer electronic; dimmer curves adjustable; Dimmer speed (step response) adjustable
- Preprogrammed in LED PC-Control 512; Light J; Light Captain
- Mains input and output for power linking up to 8 units

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x filter frame

Logistic

ROADINGER Flightcase 2x LED THA-100F/THA-120PC

Trunk case, PRO version

- With accessory compartment
- With 2 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding

- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 26,20 kg

EUROLITE LED THA-100F Theatre-Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	120 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray)
Lamp type:	LED lamp
LED:	1 x 100 W COB (chip-on-board) warm white (WW)
Color temperature:	3200K
Equipment:	Zoom manual
DMX channels:	1; 3
Cooling:	Temperature-controlled fan
Control:	DMX
Preprogrammed in:	LED PC-Control 512; Light'J; Light Captain
Projection:	Flicker-free
Beam angle:	10° - 60°
Beam angle (1/2 peak):	10 - 50°
Beam angle (1/10 peak):	12 - 60°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display
Dimensions:	Length: 37 cm Width: 33,5 cm Height: 26,5 cm
Weight:	6,30 kg
Noise classification:	Class 2 (slight noise)
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x LED THA-100F/THA-120PC

Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Accessory compartment:	10 cm x 33 cm x 42 cm
Compartment dimensions:	28,5 cm x 33 cm x 42 cm
Inside dimensions:	72 cm x 33 cm x 42 cm
Dimensions:	Width: 76 cm Depth: 37 cm Height: 53 cm
Weight:	13,60 kg