

## EUROLITE Set 2x LED THA-120PC Theater Spot + Case

2x Fresnel spot, 120 W COB LED (RGBW), extremely quiet, DMX including PRO flightcase

Art. No.: 20000364

GTIN:



**List price: 1724.31 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED THA-120PC Theater Spot

Fresnel spotlight (fresnel lens), 120 W COB LED (RGBW), extremely quiet, DMX

- Compact design
- 1 powerful LED 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Dimmer electronic; color change adjustable; color fade adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; sound to light via microphone
- Preprogrammed in LED PC-Control 512; Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Flicker-free
- With a beam angle of 3° - 43°
- With mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Installation; Trade fair and shop fitting; stage; theater; rental
- Application possibility: Suspended; on stand

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x filter frame

### Logistic

#### ROADINGER Flightcase 2x LED THA-100F/THA-120PC

Trunk case, PRO version

- With accessory compartment

- With 2 device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

Weight:	25,30 kg
---------	----------

### EUROLITE LED THA-120PC Theater Spot

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
IP classification:	IP20
Power connection:	Mains input via PowerCON (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x PowerCON (gray), mounting version
LED type:	1 x 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 6; 7
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; sound to light via microphone
Preprogrammed in:	LED PC-Control 512; Light 'J'; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	3° - 43°
Beam angle (1/2 peak):	3 - 32°
Beam angle (1/10 peak):	9 - 43°
Housing color:	Black
Attachment system:	Mounting bracket
Dimensions:	Length: 37 cm Width: 25,6 cm Depth: 36 cm
Weight:	5,85 kg
Noise classification:	Class 2 (slight noise)

#### Legal specifications

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### ROADINGER Flightcase 2x LED THA-100F/THA-120PC

Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Accessory compartment:	10 cm x 33 cm x 42 cm
Compartment dimensions:	28,5 cm x 33 cm x 42 cm
Inside dimensions:	72 cm x 33 cm x 42 cm
Dimensions:	Width: 76 cm Depth: 37 cm Height: 53 cm
Weight:	13,60 kg