



List price: 11898.81 €

incl. 19% VAT.

Features:

ALUTRUSS QUADLOCK 6082-3000 4-Way Cross Beam

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- TÜV Süd certified
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x connection Set

Logistic

ALUTRUSS QUADLOCK 6082L-30 3-Way Corner 90°

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school

Package contents

- 2 x connection Set

ALUTRUSS QUADLOCK 6082T-35 3-Way T-Piece

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school

Package contents

- 2 x connection Set

ALUTRUSS QUADLOCK 6082C-41 4-Way Cross Piece

4-point truss system

- Strong EN-AW 6082 alloy for high loads
- High-quality aluminum-tubes with 50 mm in diameter
- Low weight
- Distance center - center: 240 mm
- Easy installation
- Trusspipe: 50 mm
- Made in Europe
- For application areas such as: Theater; Trade fair and shop fitting; Clubs/dancing school

Package contents

- 3 x connection Set

ALUTRUSS QUICK-LOCK Spare Pivot with Pin

QUICK-LOCK set

- Accessories for the robust truss system with Quick-Lock
- For use with TRI/QUAD system
- Trusspipe: 50 mm
- Made in Europe

Package contents

- 2 x splint, 2 x bolt

ALUTRUSS QUADLOCK End Plate QQGP-Male M-10

Baseplate for mobile use (connectors 6082 included)

- Easy installation
- The article is delivered pre-assembled
- Trusspipe: 50 mm
- Made in Europe
- Application possibility: Standing

half cone

- M10 thread

Package contents

- 1 x plate, 4 x half cone

Technical specifications:

Weight:

300,44 kg

ALUTRUSS QUADLOCK 6082-3000 4-Way Cross Beam

| | |
|-----------------------------|--|
| Setup: | Easy installation |
| Trusspipe: | 50 mm x 2 mm |
| Welding technique: | TIG-welding |
| Welding material: | AlMg 5 |
| Alloy: | AlMgSi1 T6 |
| Color: | Alu colored |
| Strut diameter x thickness: | 16 x 2mm |
| Dimensions: | Length: 3 m Width: 29 cm Height: 29 cm |
| Weight: | 14,2 kg |

ALUTRUSS QUADLOCK 6082L-30 3-Way Corner 90°

| | |
|-----------------------------|--|
| Setup: | Easy installation |
| Trusspipe: | 50 mm x 2 mm |
| Color: | Alu colored |
| Strut diameter x thickness: | 16 x 2mm |
| Dimensions: | Length: 50 cm Width: 50 cm Height: 50 cm |
| Weight: | 7,95 kg |

ALUTRUSS QUADLOCK 6082T-35 3-Way T-Piece

| | |
|-----------------------------|--|
| Setup: | Easy installation |
| Trusspipe: | 50 mm x 2 mm |
| Color: | Alu colored |
| Strut diameter x thickness: | 16 x 2mm |
| Dimensions: | Length: 71 cm Width: 50 cm Height: 29 cm |
| Weight: | 5,9 kg |

ALUTRUSS QUADLOCK 6082C-41 4-Way Cross Piece

| | |
|-----------------------------|--|
| Setup: | Easy installation |
| Trusspipe: | 50 mm x 2 mm |
| Color: | Alu colored |
| Strut diameter x thickness: | 16 x 2mm |
| Dimensions: | Length: 71 cm Width: 71 cm Height: 29 cm |

Weight: 10,90 kg

ALUTRUSS QUICK-LOCK Spare Pivot with Pin

Trusspipe: 50 mm

Color: Alu colored

Weight: 90 g

ALUTRUSS QUADLOCK End Plate QQGP-Male M-10

Setup: Easy installation

Trusspipe: 50 mm

Material: Aluminum

Color: Alu colored

Dimensions: Length: 30,7 cm
Width: 30,7 cm
Height: 5 cm

Weight: 1,55 kg

Half cone

Thread: M10 thread
