
eurolite®

EUROLITE Set 4x LED BAR-6 QCL RGBW + 2x Soft Bag + Controller

4x Spotlight bar with 6 x 4 W 4in1 LED including soft bag and compact DMX controller

Art. No.: 20000405 GTIN:





incl. 19% VAT.

Features:

EUROLITE LED BAR-6 QCL RGBW Bar

LED bar (60cm) with 6 x 4 watt 4in1 QCL RGBW LED

- 6 powerful LEDs 4 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Light J; Colorchief
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels; small rental
- Silent operation
- Application possibility: Suspended; wall mounting Package contents
- 1 x light effect, 2 x mounting bracket, 1 x power cord, 2 x screw, 2 x washer, 1 x user manual

EUROLITE SB-205 Soft Bag

Universal softbag

Logistic

- Ideal for e.g. LED bars with 50 cm length and accessories
- With divider
- With 2 device compartments
- High-quality workmanship with nylon , black
- Interior with foam padding
- 2 carrying straps

EUROLITE DMX LED EASY Operator 4x4

Compact DMX controller for 4 LED spotlights with up to 4 colors each

- DMX controller for standard LED spotlights
- Easy handling
- 4 fixtures with RGBW LEDs can be controlled individually or in combination
- DMX channels for red, green, blue, white and master
- Various modes for the DMX channel sequence selectable
- Manual control via 4 faders
- 1 fader for direct RGBW mixing
- Adjustable strobe function
- Blackout function
- 8 integrated show programs
- Preprogrammed 8 scenes/chases
- Can transmit up to 20 DMX channels
- Control via DMX; sound to light via microphone; stand-alone
- Desktop console housing
- For application areas such as: Party room; mobile djs / entertainer
- Silent operation
- Package contents
- 1 x controller, 1 x external mains adapter, 1 x user manual

Technical specifications:

Weight:	8,10 kg

EUROLITE LED BAR-6 QCL RGBW Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	15 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	6 x 4 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling

Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Preprogrammed in:	LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Light'J; Colorchief
Projection:	Flicker-free
Beam angle:	17°
Beam angle (1/2 peak):	17°
Beam angle (1/10 peak):	33°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Material:	Aluminum casting; metal; plastic
Dimensions:	Length: 60 cm Depth: 6,5 cm Height: 10 cm
Weight:	1,66 kg
Noise classification:	Class 0 (no noise at all)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø7mm
Material:	Metal, 2 mm
Power cord	
Cable construction:	3 x 0,75 mm² H05VV-F
Cable length:	Approx. 1,1 m
Cable length: Legal specifications	Approx. 1,1 m
	Approx. 1,1 m Not designed for household room illumination
Legal specifications	

EUROLITE SB-205 Soft Bag	
Maximum load:	25 kg
Carrying strap:	2 pc/pcs
Material:	Nylon, water repellent
Color:	Black
Dimensions:	Width: 57,5 cm
	Depth: 17 cm
	Height: 12 cm
Weight:	0,30 kg

EUROLITE DMX LED EASY Operator 4x4	
Power supply:	100-240 V AC, 50/60 Hz
	9V DC 800 mA

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power consumption:	10 W	
IP classification:	IP20	
Protection class:	Protection class III	
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)	
Programs:	Preprogrammed 8 scenes/chases	
DMX channels:	Output 20	
DMX output:	3-pin XLR (F) mounting version	
Control:	DMX; sound to light via microphone; stand-alone	
Housing color:	Black	
Color:	Black	
Housing design:	Desktop console housing	
Dimensions:	Width: 20 cm	
	Depth: 11,5 cm	
	Height: 5,5 cm	
Weight:	0,86 kg	
Noise classification:	Class 0 (no noise at all)	