

# **EUROLITE Set 4x LED PAR-56 QCL sil + Case + Controller**

4x PAR-56 Spot with 9 x 8 W 4in1 LED including flightcase and compact DMX controller

Art. No.: 20000412

GTIN:









# The article is no longer in our assortment.

Features: Logistic

#### **EUROLITE LED PAR-56 QCL Short sil**

PAR-56 spot with 9 x 8 W 4in1 LED and RGBW color mixing

- Operable in stand-alone mode or via DMX
- Adjustable microphone sensitivity via control board
- Functions: Static colors, RGBW color mixture, auto mode, internal programs, dimmer and strobe settings via DMX, Master/Slave
- Equipped with 9 x 8 W 4in1 LED in red, green, blue and white
- Locking possibility at the mounting bracket
- Comfortable addressing and setting via control board with LED display and four operating buttons
- Additional controlling possibility via the EUROLITE IR-7 remote control, included in delivery
- Switch-mode power supply for operation between 100 and 240 volts
- Ready for connection via included IEC power cord with safety power plug
- Silver or black housing available
- 9 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4;
   LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain
- Flicker-free
- With a beam angle of 8°

## Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery

#### ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

Trunk case

- With 4 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- For further information about this product, please refer to the Data Sheet under "Downloads"

## **EUROLITE DMX LED EASY Operator 4x4**

Compact DMX controller for 4 LED spotlights with up to 4 colors each

- DMX controller for standard LED spotlights
- Easy handling
- 4 fixtures with RGBW LEDs can be controlled individually or in combination
- DMX channels for red, green, blue, white and master
- Various modes for the DMX channel sequence selectable
- Manual control via 4 faders
- 1 fader for direct RGBW mixing
- Adjustable strobe function
- Blackout function
- 8 integrated show programs
- Preprogrammed 8 scenes/chases )
- Can transmit up to 20 DMX channels
- Control via DMX; Sound to light via Microphone; stand-alone
- Desktop console housing
- For application areas such as: Party room; mobile djs / entertainer
- Silent operation

#### Package contents

- 1 x controller, 1 x external mains adapter, 1 x user manual

## **Technical specifications:**

Weight: 15,87 kg

### **EUROLITE LED PAR-56 QCL Short sil**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	50 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED:	9 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	4; 8; 6
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version

Preprogrammed in:  Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain  Projection:  Flicker-free  Beam angle:  8°  Beam angle (1/2 peak):  8°  Beam angle (1/10 peak):  25°  Housing color:  Silver  Dimensions:  Width: 20,5 cm Depth: 17,5 cm Height: 23 cm  Weight:  1,76 kg  Photobiological safety:  Remote control  Battery:  1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications  Special product:  Not designed for household room illumination	Control:	Stand-alone; DMX; IR remote control; Sound to light via Microphone
Beam angle:  Beam angle (1/2 peak):  Beam angle (1/10 peak):  Beam angle (1/10 peak):  Control  Beam angle (1/10 peak):  Control  Beam angle (1/10 peak):  Control  Battery:  Control  Battery:  Control  Battery:  Control  Control	Preprogrammed in:	LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR
Beam angle (1/2 peak):  Beam angle (1/10 peak):  Housing color:  Dimensions:  Width: 20,5 cm Depth: 17,5 cm Height: 23 cm  Weight:  1,76 kg  Photobiological safety:  Remote control  Battery:  1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications	Projection:	Flicker-free
Beam angle (1/10 peak):  Housing color:  Dimensions:  Width: 20,5 cm Depth: 17,5 cm Height: 23 cm  Weight:  1,76 kg  Photobiological safety:  Remote control  Battery:  1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications	Beam angle:	8°
Housing color:  Dimensions:  Width: 20,5 cm Depth: 17,5 cm Height: 23 cm  Weight:  1,76 kg  Photobiological safety:  Remote control  Battery:  1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications	Beam angle (1/2 peak):	8°
Dimensions:  Width: 20,5 cm Depth: 17,5 cm Height: 23 cm  Weight:  1,76 kg Photobiological safety: Remote control  Battery:  1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications	Beam angle (1/10 peak):	25°
Depth: 17,5 cm Height: 23 cm  Weight: 1,76 kg  Photobiological safety: Risk Group 0  Remote control  Battery: 1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications	Housing color:	Silver
Height: 23 cm  Weight: 1,76 kg  Photobiological safety: Risk Group 0  Remote control  Battery: 1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications	Dimensions:	Width: 20,5 cm
Weight: 1,76 kg  Photobiological safety: Risk Group 0  Remote control  Battery: 1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications		Depth: 17,5 cm
Photobiological safety:  Remote control  Battery:  1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications		Height: 23 cm
Remote control  Battery:  1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications	Weight:	1,76 kg
Battery:  1 x Button cell 3.0 V CR2025 lithium manganes built-in  Legal specifications	Photobiological safety:	Risk Group 0
built-in  Legal specifications	Remote control	
	Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Special product: Not designed for household room illumination	Legal specifications	
	Special product:	Not designed for household room illumination
Intended use: Show effect lighting	Intended use:	Show effect lighting

## ROADINGER Flightcase EPS-56 4x PAR-56 Spot short

25 kg
30 mm
2 pc/pcs
2 pc/pcs
Butterfly lock: 1 pc/pcs
Birch multiplex, 7 mm
Dark brown, laminated
22 cm x 22 cm x 24 cm
44 cm x 44 cm x 24 cm
Width: 48,5 cm
Depth: 48,5 cm
Height: 31 cm
7,95 kg

## **EUROLITE DMX LED EASY Operator 4x4**

Power supply:	100-240 V AC, 50/60 Hz
	9 V DC 800 mA
Power consumption:	10 W
IP classification:	IP20
Protection class:	Protection class III

Power connection:	Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Preprogrammed 8 scenes/chases )
DMX channels:	Output 20
DMX output:	3-pin XLR (F) mounting version
Control:	DMX; Sound to light via Microphone; stand-alone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 20 cm
	Depth: 11,5 cm
	Height: 5,5 cm
Weight:	860 g
Noise classification:	Class 0 (no noise at all)