

EUROLITE Set 4x AKKU Flat Light 1 silver + Soft Bag

4x flat spotlight with 15 W RGBW LED including soft bag

Art. No.: 20000423

GTIN:



Features:

- With QuickDMX transceiver - cordless, flexible and versatile
- Equipped with a 15 W QCL LED in red, green, blue and white
- Cordless and versatile
- Elegant housing for indoor use
- With integrated QuickDMX transmitter/receiver for the wireless transmission of DMX512 signals
- Operation via built-in rechargeable lithium-ion battery with up to 18 hours operating time
- Integrated automatic charging of the battery with indicator
- Stepless color blend, color change, preset colors, dimmer and strobe effect
- Dimmer speed (step response) adjustable
- Addressing and setting via Control Board with touch buttons and LCD
- Inclination angle manually adjustable via the bracket
- Charger included in delivery
- 1 LED 15 W SMD 9080 4in1 RGBW (homogenous color mix)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via master/slave function; stand-alone; IR remote control; sound to light via microphone; QuickDMX
- Flicker-free
- With a beam angle of 8°
- For application areas such as: Wedding/gala/events; small rental
- Silent operation

device

- Cordless, flexible and versatile
- Battery operation up to 18h depending on program used
- <p>EUROLITE SB-14 Soft Bag

Logistic

- <h2 class="featureSatz">Practical black soft bag, divided into 4 compartments, for 4 AKKU Flat Lights</h2>With 2 Outside pockets
- With 4 compartments
- High-quality workmanship with nylon , black, water repellent
- Interior with foam padding
- 2 carrying straps

Technical specifications:

Weight: 7.02 kg

EUROLITE AKKU Flat Light 1 sil

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz 12.6V DC 2500 mA |
| Protection class: | Protection class III |
| Power connection: | Battery/battery pack Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided) |
| Lamp type: | LED lamp |
| LED type: | 1 x 15 W SMD 9080 4in1 RGBW (homogenous color mix) |
| DMX channels: | 3; 4; 6; 8; 10 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Master/slave function; stand-alone; IR remote control; sound to light via microphone; QuickDMX |
| Fixtures available for: | LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain |
| Projection: | Flicker-free |
| Carrier frequency: | 2.4 GHz |
| Beam angle (1/2 peak): | 8° |
| Housing color: | Silver |
| Dimensions: | Width: 16.8 cm Depth: 13.8 cm Height: 6.2 cm |
| Weight: | 1.67 kg |
| Noise classification: | Class 0 (no noise at all) |
| Battery: | 1 x button cell 3.0 V CR2032 lithium manganese built-in |
| Battery pack type: | 1 x lithium ion 11.1 V, 2600 mAh, 28.86 Wh |
| Battery pack: | Battery operation up to 18h depending on program used Recharging time 4h |
| Special product: | Not designed for household room illumination |

Intended use: Show effect lighting

EUROLITE SB-14 Soft Bag

| | |
|-----------------|---|
| Carrying strap: | 2 pc/pcs |
| Material: | Nylon |
| Color: | Black, water repellent |
| Dimensions: | Width: 28 cm Depth: 22 cm Height: 18 cm |
| Weight: | 0.34 kg |

Scope of delivery:

- 1 x remote control
- 1 x device
- 1 x user manual
- 1 x external mains adapter