

EUROLITE Set 4x LED SLS-7 HCL Floor + 2x LED FE-700 + DMX LED Color Chief Controller

4x LED spotlight, 2x DMX lighting effect with beams including DMX lighting desk

GTIN:



List price: 1069.81 €

incl. 19% VAT.

Features: Logistic

EUROLITE LED SLS-7 HCL Floor

Flat LED spotlight with RGBWA+UV color mixing, incl. IR remote control

- Slim design for space-saving applications
- Enjoy perfect solid and pastel colors plus ultra violet thanks to 6-color mixing
- DMX and power terminals intelligently designed for easy wiring
- 7 powerful LEDs 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect; UV effect
- 2 integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control
- Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6;
 LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 17°
- With double bracket
- Monochrome 4 digit 7-segment LED display
- Rubber feet
- Mains input and output for power linking up to 8 units
- Available in various colors
- For application areas such as: Clubs/dancing school; wedding/gala/events; party room; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x user manual

EUROLITE LED FE-700 Flower Effect

DMX lighting effect with beams in the colors R, G, B, W, A and P, incl. IR remote control

- Precision lenses fill the room with countless rotating beams
- 6 powerful LEDs 3 W high-power R/G/B/W/A/P
- Rotation speed stepless
- Multi beam effect; flower effect; strobe effect
- 3 integrated show programs
- Direct color selection for 25 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Preprogrammed in Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW
 2; Colorchief
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; wedding/gala/events; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Suspended; on stand

Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

EUROLITE DMX LED Color Chief Controller

DMX lighting desk with innovative control concept for LED spotlights

- Easy control of LED spotlights with up to 6 colors, light bars as well as simple lighting effects
- For 8 devices or device groups, each with up to 4 segments
- Quick and easy programming
- Additional fixtures can be configured manually
- 8 color effects directly selectable
- 3 additional channels available per fixture (e.g. for rotations)
- Color wheel selection and simulation
- 24 memory spaces for scenes and chases
- Several chases and scenes can be run simultaneously
- USB port for storing program data
- Sound control via audio signal or TAP button
- Master dimming, fade time and run time easily adjustable
- Can transmit up to 240 DMX channels
- (19") 48.3 cm rack installation 3 U
- Programmable 24 scenes/chases distributed over 1 page/s
- Control via DMX; sound to light via RCA (F) mounting version; sound to light via microphone
- Firmware can be updated
- Desktop console housing
- For application areas such as: Clubs/dancing school; party room; Trade fair and shop fitting; mobile djs / entertainer; restaurants, bars and hotels
- Silent operation

Power supply:

Package contents

- 1 x controller, 1 x user manual, 1 x external mains adapter

Technical specifications:		
<u> </u>		
Weight:	14,77 kg	
EUROLITE LED SLS-7 HCL Floor		

100-240 V AC, 50/60 Hz

Power consumption:	20 W	
IP classification:	IP20	
Protection class:	Protection class I	
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)	
Power output:	1 x IEC connector (F) mounting version	
Fuse:	5 x 20 mm, T 0,5 A fuse replaceable	
Lamp type:	LED lamp	
LED type:	7 x 10 W high-power 6in1 HCL RGBWA/UV (homogenous color mix)	
Flash rate:	0 - 20 Hz	
DMX channels:	2; 3; 4; 6; 10	
DMX input:	3-pin XLR (M) mounting version	
DMX output:	3-pin XLR (F) mounting version	
Cooling:	1 x cooling fan	
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; IR remote control	
Preprogrammed in:	Light'J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief	
Projection:	Flicker-free	
Beam angle:	17°	
Beam angle (1/2 peak):	17°	
Beam angle (1/10 peak):	39°	
Wavelength:	Ultra violet (UV) 400 nm	
Housing color:	Black	
Attachment system:	Double bracket	
Display type:	Monochrome 4 digit 7-segment LED display	
Transport aid:	Rubber feet	
Material:	ABS Acrylonitrile butadiene styrene; metal	
Dimensions:	Width: 22 cm	
	Depth: 11 cm	
Weight:	Height: 21 cm	
Noise classification:	1,38 kg Class 2 (slight noise)	
Photobiological safety:	Risk Group 0	
Power cord	Mak Group o	
Cable construction:	3 x 0 75 mm² H05\/\/-F	
Cable length:	3 x 0,75 mm² H05VV-F	
Mounting bracket	Approx. 1,2 m	
Diameter mounting holes:	5 x Ø11mm	
Material:	5 x Ø11mm Metal 2 mm	
Color:	Metal, 2 mm Black	
Remote control	Sider	

EUROLITE LED FE-700 Flower Effect

Power supply:	100-240 V AC, 50/60 Hz	
Power consumption:	24 W	
IP classification:	IP20	
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)	
Power output:	1 x IEC connector (F) mounting version	
Lamp type:	LED lamp	
LED type:	6 x 3 W high-power R/G/B/W/A/P	
DMX channels:	3; 10	
DMX input:	3-pin XLR (M) mounting version	
DMX output:	3-pin XLR (F) mounting version	
Cooling:	Passive convection cooling	
Control:	Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function	
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; Colorchief	
Housing color:	Black	
Attachment system:	Mounting bracket	
Display type:	4 digit 7-segment LED display	
Material:	Metal	
Dimensions:	Width: 30 cm Depth: 20 cm Height: 31 cm	
Weight:	3,50 kg	
Noise classification:	Class 2 (slight noise); class 2 (slight noise)	
Power cord		
Cable construction:	3 x 0,75 mm² H05VV-F	
Cable length:	Approx. 1,2 m	
Mounting bracket		
Diameter mounting holes:	3 x Ø11mm; 4 x Ø5mm	
Material:	Metal, 2 mm	
Remote control		
Battery:	1 x button cell 3.0 V CR2025 lithium manganese built-in	
Legal specifications		
Special product:	Not designed for household room illumination	
Intended use:	Show effect lighting	

EUROLITE DMX LED Color Chief Controller

Power supply:	100-240 V AC, 50/60 Hz 9V DC 800 mA	
Power consumption:	7,2 W	
IP classification:	IP20	
Protection class:	Protection class III	
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)	
Programs:	Programmable 24 scenes/chases distributed over 1 page/s	
DMX channels:	Output 240	
DMX output:	1 x 3-pin XLR (F) mounting version	
Control:	DMX; sound to light via RCA (F) mounting version; sound to light via microphone	
Housing color:	Black	
Available storage media:	USB devices (FAT 32)	
USB port:	Туре А	
Color:	Black	
PC connect:	, firmware can be updated	
Housing design:	(19") 48.3 cm rack installation 3 U Desktop console housing	
Dimensions:	Width: 48,3 cm Depth: 13,35 cm Height: 8,5 cm	
Weight:	2,25 kg	
Noise classification:	Class 0 (no noise at all)	