



The article is no longer in our assortment.

Features:**OMNITRONIC UHF-201 Wireless Mic System 828.250MHz**

Wireless microphone system with UHF PLL technology

- Receiver unit and hand-held microphone with UHF PLL technology
- Operation in the low-interference UHF band
- Parallel operation of up to 4 sets is possible without any interference
- Volume control
- XLR and 6.3 mm output
- Jack cable included
- LEDs for power, carrier and audio signal
- Microphone with mute switch and color indication
- Matching pocket transmitter can be ordered separately
- Operation in the Duplex Gap 823-832 MHz
- License-free in Germany and 13 other countries
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- (19") 48.3 cm rack installation possible

Microphone

- Polar pattern: Cardioid
- Operating range up to 60m

Package contents

- 1 x receiver, 1 x antenna, 1 x external mains adapter, 1 x microphone, 1 x jack cable, 1 x user manual, 1 x declaration of conformity

Logistic

OMNITRONIC UHF-200 BP Bodypack 828.250MHz

Bodypack transmitter with lavalier microphone

- Pocket transmitter as UHF PLL system, matching receivers with the same carrier frequency
- Operation in the Duplex Gap 823-832 MHz
- Incl. lavalier microphone
- Transmitting power 10 mW
- Sensitivity adjustable
- Power LED
- Mute switch
- Operation via 2 x 1.5 V batteries, type AA
- License-free in Germany and 13 other EU countries
- Polar pattern: Cardioid
- UHF 823 - 832 MHz License-free and approved in large parts of Europe

Technical specifications:

Weight: 830 g

OMNITRONIC UHF-201 Wireless Mic System 828.250MHz

| | |
|----------------------|---|
| Type: | Wireless set |
| Number of channels: | 1 |
| Frequency range: | 40 - 18000 Hz |
| S/N ratio: | >105 dB |
| THD: | <0,5 % at 1 kHz |
| Frequency band: | UHF 823 - 832 MHz |
| Carrier frequency: | 828,250 MHz |
| RF power output: | 10 mW |
| Modulation: | F3F |
| Frequency selection: | Fixed frequencies |
| Connections: | Output: Microphone via 1 x 3-pin XLR Output: Microphone via 1 x 6.3 mm plug (unbal.) |
| Housing design: | (19") 48.3 cm rack installation possible |
| Weight: | 720 g |
| Receiver | |
| Power supply: | 100-240 V AC, 50/60 Hz 12 V DC 500 mA |
| Power consumption: | 1,75 W |
| Power connection: | Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided) |
| Microphone | |
| Power supply: | 3 V DC |
| Power connection: | Battery/battery pack |
| Capsule type: | Dynamic |
| Polar pattern: | Cardioid |
| Battery: | 2 x Mignon (AA) (not included) |
| Range: | Range up to 60m |
| Switch: | On/off switch; Mute control |

| | |
|-------------|-------------------------------------|
| Material: | Plastic |
| Dimensions: | Length: 26,5 cm Diameter: Ø 5 cm |
| Weight: | 185 g |

OMNITRONIC UHF-200 BP Bodypack 828.250MHz

| | |
|----------------------|--|
| Type: | Bodypack with microphone |
| Capsule type: | Dynamic |
| Polar pattern: | Cardioid |
| Battery: | 2 x 1.5 V AA Mignon R06 zinc carbon included |
| Frequency range: | 40 - 18000 Hz |
| Frequency band: | UHF 823 - 832 MHz |
| Frequency selection: | Fixed frequencies |
| Dimensions: | Width: 65 cm Depth: 20 cm Height: 2,5 cm |
| Carrier frequency: | 828.250 MHz |
| Coverage: | 50 m (with line-of-sight) |
| RF power output: | 10 mW |
| Modulation method: | F3E |
| S/N ratio: | >105 dB |
| Selectivity: | >80 dB |
| T.H.D.: | <0.5 % at 1 kHz |
| Connection: | 3.5 mm jack |
| Weight: | 75 g |