

## EUROLITE Set LED KLS Laser Bar FX Light Set + M-4 Speaker-System Stand. No.: 20000451

LED KLS Laser Bar FX Light Set including aluminum speaker stand

GTIN:



**List price: 529.55 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED KLS Laser Bar FX Light Set

Bar with 2 derbies, 2 spots, white strobe LEDs, laser (RG, 2M), foot switch

- Crossbar with integrated DMX control unit and stand sleeve
  - 2 laser diodes project hundreds of red and green laser beams
  - 2 rotating derbies for mirror ball effects
  - For application areas such as: Wedding/gala/events; mobile use; Party room; mobile djs / entertainer; small rental
  - When fog is used, this effect becomes especially attractive
  - 37 integrated show programs
  - The device is cooled by cooling fan
  - Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch; Master/slave function
  - With Mounting bracket
  - Preprogrammed in Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3
  - Mains input and output for power linking up to 8 units
  - Laser; multi beam effect; Strobe effect; flower effect
  - Application possibility: On stand
- laser**
- Laser class 2M <BR> does not require additional protective measures or appointment of a laser safety officer
- spotlight**
- 3 powerful LEDs 3 W high-power 3in1 TCL RGB (homogenous color mix)<BR>2 spots controlled separately
  - With a beam angle of 13°
- light effect**

### Logistic

- 3 powerful LEDs 1 W high-power R/G/B<BR>2 spots controlled separately  
**bar**
- 4 powerful LEDs 1 W high-power cold white (CW)<BR> LEDs controlled separately  
**Package contents**
- 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x foot control, 1 x remote control, 2 x battery, 2 x mounting bracket, 2 x knurled screw, 1 x bag, 2 x washer

#### OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height

#### Package contents

- 1 x user manual

### Technical specifications:

---

#### EUROLITE LED KLS Laser Bar FX Light Set

|                       |  |
|-----------------------|--|
| Power supply:         | 100-240 V AC, 50/60 Hz   |
| Power consumption:    | 50 W   |
| IP classification:    | IP20   |
| Protection class:     | Protection class I   |
| Power connection:     | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)               |
| Power output:         | 1 x IEC connector (F) mounting version   |
| Device fuse:          | 5 x 20 mm, F 1 A Fuse replaceable  |
| Lamp type:            | LED lamp   |
| Flash rate:           | 0 - 30 Hz  |
| DMX channels:         | 3; 5; 9; 27  |
| DMX input:            | 1 x 3-pin XLR (M) mounting version   |
| DMX output:           | 1 x 3-pin XLR (F) mounting version   |
| Cooling:              | Cooling fan  |
| Control:              | Stand-alone; DMX; IR remote control; Sound to light via Microphone; Wireless footswitch; Master/slave function |
| Preprogrammed in:     | Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3                              |
| Housing color:        | Black  |
| Attachment system:    | 2x Mounting bracket  |
| Dimensions:           | Width: 1,09 m<br>Depth: 14,5 cm<br>Height: 37 cm   |
| Weight:               | 9,05 kg  |
| Noise classification: | Class 2 (slight noise)   |
| <b>Laser</b>          |  |
| Laser class:          | 2M   |
| Laser color:          | R/G  |
| Laser module:         | Red (R) 100 mW 650nm   |

Green (G) 30 mW 532nm

---

Spotlight

---

|                         |  |
|-------------------------|--|
| LED:                    | 3 x 3 W high-power 3in1 TCL RGB (homogenous color mix) |
| Beam angle:             | 13°  |
| Beam angle (1/2 peak):  | 13°  |
| Beam angle (1/10 peak): | 20°  |

---

Light effect

---

|      |                          |
|------|--------------------------|
| LED: | 3 x 1 W high-power R/G/B |
|------|--------------------------|

---

Bar

---

|                        |                                    |
|------------------------|------------------------------------|
| LED:                   | 4 x 1 W high-power cold white (CW) |
| Beam angle (1/2 peak): | 7°                                 |

---

Foot control

---

|          |   |
|----------|---|
| Battery: | 1 x 9.0 V E block 6LR61 alkaline manganese included |
|----------|---|

---

Remote control

---

|          |   |
|----------|---|
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
|----------|---|

---

**OMNITRONIC M-4 Speaker-System Stand**

---

|                            |   |
|----------------------------|---|
| Maximum carrying capacity: | 18 kg   |
| Tube diameter sector:      | 38 - 35 mm  |
| Height:                    | Maximum: 345 cm<br>Minimum: 140 cm<br>Adjustable in 10 steps with locking pin |
| Attachment system:         | Ø 35mm  |
| Type (general stands):     | Speaker stand/manual  |
| Material:                  | Aluminum  |
| Color:                     | Black   |
| Transport dimensions:      | 1,4 m x 13,5 cm   |
| Weight:                    | 3,30 kg   |

---