

## EUROLITE Set LED KLS-170 Compact Light Set + M-4 Speaker-System Stand No.: 20000453

LED KLS-170 Compact Light Set including aluminum speaker stand

GTIN:



**The article is no longer in our assortment.**

### Features:

#### EUROLITE LED KLS-170 Compact Light Set

Bar with 4 RGB spots, cold white + UV strobe LEDs, foot switch and carrying bag

- Compact lightweight
- Crossbar with integrated DMX control unit and stand sleeve
- Silent operation
- 31 integrated show programs
- Control via stand-alone; DMX; Wireless footswitch; IR remote control; Sound to light via Microphone; Master/slave function
- Preprogrammed in EASY SHOW 1; Light´J; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3
- With Mounting bracket
- Mains input and output for power linking up to 8 units
- For application areas such as: Party room; mobile use; mobile djs / entertainer; small rental
- Application possibility: On stand

#### spotlight

- 3 powerful LEDs 9 W high-power 3in1 TCL RGB (homogenous color mix)<BR> spots controlled separately

#### bar

- 4 powerful LEDs 2 W high-power 2in1 BCL CW/UV (homogenous color mix)<BR> LEDs controlled separately

#### Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x bag, 1 x foot control, 1 x remote control, 2 x battery, 2 x mounting bracket, 2 x knurled screw, 2 x washer

### Logistic

## OMNITRONIC M-4 Speaker-System Stand

Aluminum speaker stand, height adjustable 140-345 cm, maximum load 18 kg

- Durable aluminum version
- Tube diameter: Ø 35 mm
- Adjustable height

### Package contents

- 1 x user manual

## Technical specifications:

---

Weight: 9,55 kg

---

## EUROLITE LED KLS-170 Compact Light Set

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	90 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	IEC connector (F) mounting version
Lamp type:	LED lamp
DMX channels:	3; 6; 16; 25
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; Wireless footswitch; IR remote control; Sound to light via Microphone; Master/slave function
Preprogrammed in:	EASY SHOW 1; Light 'J'; LED PC-Control 512; Light Captain; EASY SHOW 2; EASY SHOW 3
Beam angle:	13°
Beam angle (1/2 peak):	13°
Beam angle (1/10 peak):	25°
Housing color:	Black
Attachment system:	2x Mounting bracket
Dimensions:	Width: 1,03 m Depth: 55 cm Height: 24 cm
Weight:	6,25 kg
Noise classification:	Class 0 (no noise at all)
Spotlight	
LED:	3 x 9 W high-power 3in1 TCL RGB (homogenous color mix)

Bar

---

LED:	4 x 2 W high-power 2in1 BCL CW/UV (homogenous color mix)
Flash rate:	0 - 30 Hz
Foot control	
Battery:	1 x 9.0 V E block 6F22 zinc carbon included
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **OMNITRONIC M-4 Speaker-System Stand**

Maximum carrying capacity:	18 kg
Tube diameter sector:	38 - 35 mm
Height:	Maximum: 345 cm Minimum: 140 cm Adjustable in 10 steps with locking pin
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Aluminum
Color:	Black
Transport dimensions:	1,4 m x 13,5 cm
Weight:	3,30 kg