

## EUROLITE Set 4x AKKU Flat Light 3 sil + Case

4x flat spotlight with 3 x 8 W RGBW LED including PRO flightcase

Art. No.: 20000471

GTIN:



**The article is no longer in our assortment.**

### Features:

#### EUROLITE AKKU Flat Light 3 sil

Flat spotlight with 3 x 8 W RGBW LED, QuickDMX transceiver and bracket

- Integrated QuickDMX transceiver for wireless DMX control
- Elegant housing for indoor use
- Battery operation up to 16h depending on program used
- 3 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; QuickDMX; Sound to light via Microphone; IR remote control
- Flicker-free
- With a beam angle of 12°
- With Mounting bracket
- Various versions available
- With a KENSINGTON LOCK theft protection
- For application areas such as: Small rental; Wedding/gala/events
- Dimmer curves with adjustable response; color blend stepless; color change adjustable; colors preset; Dimmer electronic
- Preprogrammed in Light´J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
- Silent operation
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator

#### Package contents

- 1 x device, 1 x user manual, 1 x external mains adapter, 1 x remote control, 1 x declaration of conformity, 1 x power cord

### Logistic

## ROADINGER Flightcase 4x AKKU Flat Light Series

Carrying case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 10,63 kg

---

### EUROLITE AKKU Flat Light 3 sil

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 2,5 A
Pin configuration:	Inside + / outside -
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via Coaxial power connector (M) mounting version power supply cord with Euro plug (provided)
Battery pack type:	1 x lithium ion 11,1 V, 5200 mAh, 57,72 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED:	3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix)
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Stand-alone; QuickDMX; Sound to light via Microphone; IR remote control
Preprogrammed in:	Light J; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	30°
Housing color:	Silver

Attachment system:	Mounting bracket
Theft protection:	KENSINGTON LOCK
Dimensions:	Width: 16,8 cm Depth: 13,8 cm Height: 6,2 cm
Weight:	1,62 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x Button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 4x AKKU Flat Light Series**

Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 1 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Compartment dimensions:	7 cm x 18,5 cm x 9 cm
Accessory compartment:	38 cm x 6,5 cm x 12 cm
Inside dimensions:	38 cm x 25 cm x 12 cm
Dimensions:	Width: 42 cm Depth: 31 cm Height: 20 cm
Weight:	4,15 kg