

## EUROLITE Set LED Umbrella 140 + BS-2 EU

LED Umbrella with high steel speaker stand and adapter

Art. No.: 20000489

GTIN:



### Features:

- DMX-controllable lighting effect umbrella with 114 SMD RGB LEDs, distributed in 7 segments
- Segments can be controlled individually via DMX
- 6 segments make the surface of the umbrella shine, one segment in the middle shines directly at the audience
- Perfect as stage background and eye-catcher for decorative purposes in shops, display windows, fair stands, hotels, bars and clubs
- Can be mounted to a lighting stand or trussing - the umbrella's angle can be adjusted
- Easy transport (can be folded), setup and installation
- Covers a large area with a diameter of 140 cm
- Built-in auto and music show programs
- Supports QuickDMX - the wireless DMX-system from Eurolite
- Built-in phantom-powered USB port for QuickDMX receivers (accessories)
- Stepless RGB color mixture, dimmer and strobe effect
- Addressing via control panel with 4-digit LED display
- Appropriate control unit included in the delivery
- Power connection via P-Con jack and included power cable with safety plug
- 114 LEDs SMD 5050 3in1 R/G/B (homogenous color mix)
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- <p>OMNITRONIC BS-2 EU Loudspeakerstand
- <h2 class="featureSatz">High steel speaker stand, height adjustable 117-205 cm, maximum load 50 kg</h2>Height adjustable, with locking pin
- Tube diameter: Ø 35 mm

### Logistic

- Adjustable height
- Made in Europe
- <p>EUROLITE SPA-10S Adapter
- <h2 class="featureSatz">For 35 mm tube with screw thread and M10 wing bolt, max. load WLL 100 kg</h2>Adapter for installing a spot, speaker system etc. on a stand
- M10 wing bolt
- M10 thread

## Technical specifications:

---

Weight: 8.35 kg

---

### EUROLITE LED Umbrella 140

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	20 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	114 x SMD 5050 3in1 R/G/B (homogenous color mix)
DMX channels:	6; 24
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Fixtures available for:	Light'J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Dimensions:	Diameter: Ø 140 cm
Weight:	3.07 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

### OMNITRONIC BS-2 EU Loudspeakerstand

Maximum carrying capacity:	50 kg
Height:	Maximum: 205 cm Minimum: 117 cm
Attachment system:	Ø 35mm
Type (general stands):	Speaker stand/manual
Material:	Steel
Color:	Black
Transport dimensions:	110 cm x 17 cm x 14 cm

Weight: 4.90 kg

---

#### **EUROLITE SPA-10S Adapter**

Maximum load BGV C1 (8-fold):	50 kg
Maximum load WLL (4-fold):	100 kg
Attachment system:	Ø 35mm
Type (general stands):	Accessory
Material:	Steel, powder-coated
Plate:	1.3 cm Ø 6 cm
Thread:	M10 thread x 25 mm
Dimensions:	Height: 13 cm Diameter: Ø 6 cm
Weight:	0.38 kg

---

#### **Scope of delivery:**

---

##### **1 x EUROLITE LED Umbrella 140**

1 x omega bracket  
1 x device  
1 x user manual  
1 x power cord  
1 x multipin cable  
1 x umbrella

##### **1 x OMNITRONIC BS-2 EU Loudspeakerstand**

1 x stand

##### **1 x EUROLITE SPA-10S Adapter**

1 x adapter  
1 x user manual