
Party-Accu-Camping Set

Battery powered party set with portable PA system and 3 lighting effects

Art. No.: 20000498

GTIN:



The article is no longer in our assortment.

Features:

OMNITRONIC WAMS-65BT Wireless PA System

Portable 6.5" PA with wireless microphone, audio player, Bluetooth and 40 W peak power

- Portable all-in-one PA system with 40 watts output power
- 4-channel power mixer
- 2-way bass-reflex system
- SD card slot and USB port
- 1 microphone input (XLR) with adjustable reverb effect
- UHF receiver unit and matching wireless microphone
- Power-efficient and battery-saving class D amplifier
- Tone control and master control
- UHF 863 - 865 MHz License-free and approved in Europe
- For application areas such as: Theater; mobile use; Wedding/gala/events; product presentations and lectures
- Black metal grille
- Rugged carrying handle
- Integrated automatic charging of the battery
- The device is cooled by passive convection cooling

Battery pack

- Battery pack must be ordered separately
- Battery operation up to 4h
- Cordless, flexible and versatile

Audio player

- Control via Bluetooth; IR remote control
- 4 digit 7-segment LED display
- 2.4 GHz license-free worldwide
- Bluetooth: Operating range up to 10m

Logistic

Microphone

- Polar pattern: Cardioid
- Operating range up to 30m

Remote control

- Operating range up to 10m

Package contents

- 1 x device, 1 x power cord, 1 x microphone, 1 x remote control, 1 x user manual, 1 x declaration of conformity

Akku 12V/2900mAh WAMS-05 / WAMS-65

- 1 x device

EUROLITE AKKU Mini PARTY RGBW Spot

DMX spotlight with 12 x 1 W LED in the colors red, green, blue and white

- Equipped with twelve 1 W LEDs - 3 x red, 3 x green, 3 x blue and 3 x white
- Small and compact, easy to transport, ideal for mobile use
- Operation via built-in rechargeable lithium-ion battery with min. 3 hours operating time
- Built-in auto and music show programs
- Functions: static colors, RGBW color mixture, internal programs, color change with diverse settings, dimmer and strobe settings
- Addressing via control panel with 4-digit LED display
- Additional controlling possibility via EUROLITE IR-25 remote control; included in delivery
- Built-in charging function via included USB charger
- Can also be charged via USB power banks
- Mounting bracket for ceiling or wall mounting
- Additional bracket for floor use
- Switch-mode power supply for operation between 100 and 240 volts
- 12 powerful LEDs 1 W high-power R/G/B/W (homogenous color mix)
- Strobe effect
- The device is cooled by cooling fan
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function
- Preprogrammed in Light J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
- With a beam angle of 12°
- 4 digit 7-segment LED display
- For application areas such as: Gift idea

device

- Cordless, flexible and versatile
- Battery operation up to 3h depending on program used

Package contents

- 1 x spotlight, 1 x user manual, 1 x external mains adapter, 1 x remote control, 1 x battery

EUROLITE AKKU BEL-15 Beam tc

Handy battery-powered beam effect with up to 5 beams, transparent housing

- Powerful battery-powered beam effect in a pocket housing
- 5 powerful LEDs 3 W high-power R/G/B/W/A
- Color change adjustable; color fade adjustable
- Multi beam effect; Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; IR remote control; Sound to light via Microphone
- With Mounting bracket
- Cordless, flexible and versatile
- Battery operation up to 4h

Package contents

- 1 x device, 1 x external mains adapter, 1 x remote control, 1 x user manual

EUROLITE AKKU BEK-10 Kaleidoscope tc

Handy battery-powered kaleidoscope effect, transparent housing

- Powerful battery-powered Kaleidoscope Effect in a pocket housing

- Equipped with one bright 4in1 LED with 10 W in the colors red, green, blue, white
 - Ideal for mobile use thanks to quick setup and rechargeable lithium-ion battery pack (up to 4 hours operating time)
 - Transparent white plastic housing with plastic bracket
 - Functions: Auto mode, automatic color change, fading colors, strobe effect
 - Charger included in delivery
 - Switch-mode power supply for operation between 100 and 240 volts
 - 1 powerful LED 10 W high-power 4in1 QCL RGBW
 - Flower effect; gobo effect
 - The device is cooled by passive convection cooling
 - Control via IR remote control; Sound to light via Microphone
- device**
- Cordless, flexible and versatile
 - Battery operation up to 4h depending on program used
- Package contents**
- 1 x device, 1 x external mains adapter, 1 x remote control, 1 x user manual

Technical specifications:

Weight: 6,70 kg

OMNITRONIC WAMS-65BT Wireless PA System

Power supply:	100-240 V AC, 50/60 Hz Or 12 V DC
Power consumption:	60 W
IP classification:	IP20
Protection class:	Protection class I
Output power:	40 W RMS
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) Battery/battery pack (not included)
Frequency range:	62 - 18000 Hz
THD:	<0,5 % at 1 kHz
Cooling:	Passive convection cooling
Frequency band:	UHF 863 - 865 MHz
Carrier frequency:	865 MHz
Frequency stability:	± 0,005 %
Frequency selection:	Fixed frequencies
Housing color:	Black
Attachment system:	Flange: Ø 35mm
Circuitry:	Class D
Control elements:	Echo effect control, Audio player
Status LED:	Power, peak, ON AIR, signal, charge status indicator
Connections:	Input: Microphone via 1 x 3-pin XLR Input: line via 1 x stereo RCA Output: line via 1 x 6.3 mm plug (unbal.)

Channels:	Microphon chanal: 1 x mono via XLR, channel control via Rotary dial Input chanel: 1 x stereo via RCA, channel control via Rotary dial Input chanel: 1 x stereo via Audio player, channel control via Rotary dial Input chanel: 1 x mono via Radio, channel control via Rotary dial Master output: 1 x mono, channel control via Rotary dial, tone control EQ
Speaker:	1 x woofer 6,5" 1 x Tweeter 1"
Type of speaker:	Compact cabinet speaker; Wireless PA system
Type of construction:	Vented
Carrying handle:	1 pc/pcs
Material:	ABS Acrylonitrile butadiene styrene
Color:	Black
Dimensions:	Width: 23,5 cm Depth: 22 cm Height: 35 cm
Weight:	4,15 kg
Battery pack	
Battery pack type:	1 x lead 12 V, 2900 mAh,
Battery pack:	Battery operation up to 4h Recharging time 4h
Audio player	
Control:	Bluetooth; IR remote control
Bluetooth device name:	Omnitronic
Audio player:	USB + SD + Bluetooth
Range:	Bluetooth: range up to 10m
Frequency band:	2.4 GHz
Display type:	4 digit 7-segment LED display
Music format:	MP3, WAV
Available storage media:	USB devices/SD cards max. 32GB (FAT 32)
Microphone	
Power supply:	3 V DC
Power connection:	Battery/battery pack
Capsule type:	Dynamic
Polar pattern:	Cardioid
Battery:	2 x Mignon (AA) (not included)
Range:	Range up to 30m
RF power output:	10 mW
Modulation:	FM
Switch:	On/off/mute switch
Material:	Plastic
Dimensions:	Length: 26 cm Diameter: Ø 4 cm
Weight:	115 g

Remote control	
Power supply:	3 V DC
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Range:	Range up to 10m

Akku 12V/2900mAh WAMS-05 / WAMS-65

Weight:	1,094 kg
---------	----------

EUROLITE AKKU Mini PARTy RGBW Spot

Power supply:	5 V DC
Power consumption:	10 W
IP classification:	IP20
Power connection:	Battery/battery pack Mains input via micro USB (F) mounting version power supply cord with AC adapter (provided)
Lamp type:	LED lamp
LED:	12 x 1 W high-power R/G/B/W (homogenous color mix)
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Cooling fan
Control:	Stand-alone; DMX; Sound to light via Microphone; Master/slave function
Preprogrammed in:	Light J; LED PC-Control 512; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE
Beam angle:	12°
Beam angle (1/2 peak):	12°
Beam angle (1/10 peak):	27°
Housing color:	Black
Display type:	4 digit 7-segment LED display
Dimensions:	Width: 16,2 cm Depth: 11,7 cm Height: 13,3 cm
Weight:	600 g
Device	
Battery pack type:	1 x lithium ion 3,7 V, 2000 mAh, 7,4 Wh
Battery pack:	Battery operation up to 3h depending on program used Recharging time 3h
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	

Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE AKKU BEL-15 Beam tc

Power supply:	100-240 V AC, 50/60 Hz 3,7 V DC 2,2 A
Power consumption:	9,2 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Battery pack type:	1 x lithium ion 3,7 V, 2200 mAh, 8 Wh
Battery pack:	Battery operation up to 4h Recharging time 4,5h
Lamp type:	LED lamp
LED:	5 x 3 W high-power R/G/B/W/A
Cooling:	Passive convection cooling
Control:	Stand-alone; IR remote control; Sound to light via Microphone
Housing color:	Clear
Attachment system:	Mounting bracket
Dimensions:	Width: 14,6 cm Depth: 15,5 cm Height: 15 cm
Weight:	390 g
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE AKKU BEK-10 Kaleidoscope tc

Power supply:	100-240 V AC, 50/60 Hz 3,7 V AC 2,2 A
Pin configuration:	Inside + / outside -
Power consumption:	9,2 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Battery/battery pack Mains input via Coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Lamp type:	LED lamp

LED:	1 x 10 W high-power 4in1 QCL RGBW
Cooling:	Passive convection cooling
Control:	IR remote control; Sound to light via Microphone
Housing color:	Clear
Dimensions:	Width: 14,6 cm Depth: 15,5 cm Height: 11,5 cm
Weight:	460 g
Device	
Battery pack type:	1 x lithium ion 3,7 V, 2200 mAh, 8 Wh
Battery pack:	Battery operation up to 4h depending on program used Recharging time 4,5h
Remote control	
Battery:	1 x Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting