

## OMNITRONIC PA Set AZX active M

2x AZX-115A PA Subwoofer active 400W, 2x AZX-212A 2-way Top active 250W and 2x Distance Tube

Art. No.: 20000527

GTIN:



**List price: 1890.91 €**

incl. 19% VAT.

### Features:

#### OMNITRONIC AZX-115A PA Subwoofer active 400W

Active 15" PA bassreflex subwoofer, 400 W RMS

- 38 cm (15") bass speaker with 63 mm voice coil
- Class D amplifier with 400 W
- XLR inputs and parallel outputs L/R
- XLR output L/R with high-pass filter
- Adjustable crossover frequency 80-200 Hz
- Black metal grille with acoustic foam
- Rugged carrying handle
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental

#### Package contents

- 1 x bass, 1 x user manual, 1 x power cord

### Logistic

#### OMNITRONIC AZX-212A 2-way Top active 250W

Active speaker with 12" woofer, 1,35" driver, 200 W RMS LF, 50 W RMS HF

- 2-way bass-reflex enclosure with 30 cm woofer and 3.5 cm titanium driver
- Balanced signal input XLR/6.3 mm jack, switchable mic/line
- HF adjustment -4 dB, -2 dB, 0 dB
- Dual flange
- With rigging points
- Black metal grille with acoustic foam
- Rugged carrying handle
- Application possibility: Standing; suspended; monitoring; on stand

- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; rental

#### Package contents

- 1 x user manual, 1 x power cord, 1 x compact cabinet speaker

### OMNITRONIC Distance Tube Subwoofer/Satellite M20

Variable distance tube, M20 thread, height adjustable 75-130 cm, max. load 30 kg

- Connecting tube for satellite systems
- Locking screw and bolt
- Powder-coated steel version
- Adjustable height
- M20 thread

#### Package contents

- 1 x distance tube, 1 x user manual

### Technical specifications:

|         |          |
|---------|----------|
| Weight: | 92,40 kg |
|---------|----------|

### OMNITRONIC AZX-115A PA Subwoofer active 400W

|                       |  |
|-----------------------|--|
| Power supply:         | 230 V AC, 50 Hz  |
| Power consumption:    | 650 W  |
| Protection class:     | Protection class I   |
| Power connection:     | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)       |
| Device fuse:          | 5 x 20 mm, T 3,15 A fuse replaceable   |
| Power:                | Rated: 400W RMS  |
| Frequency range:      | 40 - 250 Hz  |
| Sensitivity:          | 94 dB (1W/1m)  |
| Attachment system:    | M20 thread   |
| Circuitry:            | Class D  |
| Control elements:     | Phase reversal switch  |
| Controls:             | Limiter  |
| Status LED:           | Limit, power, signal   |
| Connections:          | Input: line via 2 x 3-pin XLR<br>Output: line via 2 x 3-pin XLR<br>Output: high-pass via 2 x 3-pin XLR |
| Crossover frequency:  | 80-200 Hz  |
| Speaker:              | 1 x woofer 15"<br>Basket material: steel<br>Voice coil lows 2,5"                                       |
| Type of speaker:      | Subwoofer  |
| Type of construction: | Vented   |
| Carrying handle:      | 1 pc/pcs   |
| Material:             | MDF (medium density fiberboard), 15 mm   |
| Color:                | Black, textured coating, painted   |

|             |               |
|-------------|---------------|
| Dimensions: | Width: 53 cm  |
|             | Depth: 55 cm  |
|             | Height: 47 cm |
| Weight:     | 26,15 kg      |

#### OMNITRONIC AZX-212A 2-way Top active 250W

|                    |  |
|--------------------|--|
| Power supply:      | 230 V AC, 50 Hz  |
| Power consumption: | 650 W  |
| Protection class:  | Protection class I   |
| Power connection:  | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)   |
| Power:             | Rated: 200W RMS LF<br>Rated: 50W RMS HF  |
| Frequency range:   | 55 - 20000 Hz  |
| Sensitivity:       | 95 dB (1W/1m)  |
| Attachment system: | Dual flange: Ø 35mm (0°/5°)  |
| Flying points:     | 7 x M10 thread   |
| Circuitry:         | Class D Biamp  |
| Control elements:  | Power switch, Input sensitivity switch, tone control, level control  |
| Controls:          | Limiter  |
| Status LED:        | Limit, power, signal   |
| Connections:       | Input: 1 x 3-pin XLR/6.35mm jack (F) combination socket (mounting version)<br>Output: line via 1 x 3-pin XLR   |
| Input channels:    | 1 x mono with mic-line switch via Combination socket (XLR/jack), channel control via rotary dial   |
| Equalizer:         | Master: 1 x 2-band tone control  |
| Speaker:           | Woofer 12" with ferrit magnet<br>Basket material: steel<br>Conematerial: cardboard/paper<br>Voice coil lows 2"<br>Voice coil compression tweeter highs 1,35" |
| Type of speaker:   | Compact cabinet speaker  |
| Carrying handle:   | 1 pc/pcs   |
| Material:          | MDF (medium density fiberboard), 15 mm   |
| Color:             | Black, textured coating, painted   |
| Dimensions:        | Width: 37 cm<br>Depth: 35,2 cm<br>Height: 62,2 cm  |
| Weight:            | 19,15 kg   |

#### OMNITRONIC Distance Tube Subwoofer/Satellite M20

|                            |            |
|----------------------------|------------|
| Maximum carrying capacity: | 30 kg      |
| Tube diameter sector:      | 41 - 35 mm |

|                        |                                   |
|------------------------|-----------------------------------|
| Height:                | Maximum: 130 cm<br>Minimum: 75 cm |
| Attachment system:     | Ø 35mm                            |
| Type (general stands): | Distance tube                     |
| Color:                 | Black                             |
| Thread:                | M20 thread                        |
| Weight:                | 0,90 kg                           |