eurolite®

EUROLITE Set LED Strip RGB 5m + RF Controller + Transformer 12V

LED Strip RGB 5m, wireless remote control and Transformer 12V

Art. No.: 20000554 GTIN:







The article is no longer in our assortment.

Features:

EUROLITE LED Strip 150 5m 5050 RGB 12V

Flexible LED strip for indoor use

- Flexible LED strip for decorative lighting
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- 150 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
- Control via system controller (optional)
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation
- Package contents
- 1 x illuminant, 1 x user manual

EUROLITE LED Strip RGB RF Controller

3-channel LED controller with wireless remote control for RGB LED strips 12-24V

- For controlling RGB LED strips 12-24 V
- Color selection via touch-sensitive color wheel
- RJ45 jacks for serial connection
- Dimmer electronic; program speed adjustable
- 10 integrated show programs
- Control via wireless remote control
- Operating range up to 20m Package contents

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

EUROLITE Electr. LED Transformer, 12V, 4A

Stabilized LED power supply unit DC 12 V, 4 A

- Especially for LED installations
- Input voltage AC 100-240 V
- Package contents
- 1 x external mains adapter

Technical specifications:

Weight:

0,56 kg

EUROLITE LED Strip 150 5m 5050 RGB 12V

Power supply:	12V DC
Power consumption:	36 W
IP classification:	IP20
Power connection:	Fixed supply cord with open wires
Cable length:	0,15 m
LED type:	150 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Control:	System controller (optional)
Standing/fixation:	Self adhesive
Lamps/meter:	30 pc/pcs
Power/meter:	7,2 W
Lamps/tube:	150 pc/pcs
Lamp distance:	33 mm
Cutting mark:	10 cm
Luminous flux (Lumen) per meter:	300 lm/m
Housing color:	White
Dimensions:	Length: 500 cm Width: 1 cm
Weight:	0,11 kg
Noise classification:	Class 0 (no noise at all)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

EUROLITE LED Strip RGB RF Controller

Power supply:	12/24V DC
Power consumption:	Max. 360 W 12 V DC
	Max. 720 W 24 V DC
	120 W 12 V DC per channal
	240 W 24 V DC per channal

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Max. 3 x 10 A per channal
Mains input via screw terminal
4 x screw terminal
Micro (AAA) (not included)
Wireless remote control
Range up to 20m
433,920 MHz
Signal via 2 x RJ-45 (F) mounting version
Screw terminal
Length: 9 cm
Width: 9 cm
Height: 2,4 cm
0,29 kg
Height: 2,2 cm

EUROLITE Electr. LED Transformer, 12V, 4A

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class II
Power connection:	Mains input via screw terminal
Power output:	Screw terminal
Housing color:	White matte
Controls:	Overload; short-circuit; overheat
Output:	12V DC, stabilized; 4 A;
Material:	Plastic
Dimensions:	Length: 18 cm
	Width: 4 cm
	Height: 2,5 cm
Weight:	0,16 kg