# eurolite®

EUROLITE Set LED Strip RGB 5m + RF Controller + Wandpanel + Trafo 24VArt. No.: 20000557 LED IP Strip 5m, wireless remote control, wireless wall dimmer and Transformer 24V



# The article is no longer in our assortment.

#### Features:

#### EUROLITE LED IP Strip 150 5m RGB 24V

Flexible 3in1 TCL RGB LED strip for indoor and outdoor use, 24 V

- Flexible LED strip for decorative lighting
- Can be cut into segments of variable size
- Self-adhesive rear side
- Supplied on a plastic reel
- 150 powerful LEDs SMD 5050 3in1 TCL RGB (homogenous color mix)
- Control via system controller
- Suitable for outdoor use
- For application areas such as: Trade fair and shop fitting; clubs/dancing school; installation; restaurants, bars and hotels
- Silent operation
  Package contents
- 1 x illuminant, 1 x user manual

#### EUROLITE LED Strip RGB RF Controller

3-channel LED controller with wireless remote control for RGB LED strips 12-24V

- For controlling RGB LED strips 12-24 V
- Color selection via touch-sensitive color wheel
- RJ45 jacks for serial connection
- Dimmer electronic; program speed adjustable
- 10 integrated show programs
- Control via wireless remote control
- Operating range up to 20m



Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

#### Package contents

1 x controller, 1 x transmitter, 1 x user manual, 1 x declaration of conformity

#### EUROLITE LED Strip Wall Panel for RGB RF Controller

Wireless wall dimmer for RGB LED strips

- For controlling RGB LED strips 12-24 V
- Color wheel selection
- Terminals for connecting the power supply (100-240 V)
- Program speed adjustable; Dimmer electronic
- 10 integrated show programs
- Operating range up to 20m
- Flush mounting
- Finery housing (optional) Package contents
- 1 x remote control, 1 x user manual, 1 x declaration of conformity

#### EUROLITE Electr. LED Transformer, 24V, 2A

Stabilized LED power supply unit DC 24 V, 2 A

- Especially for LED installations
- Input voltage AC 100-240 V Package contents
- 1 x external mains adapter

# **Technical specifications:**

Weight:

0,74 kg

#### EUROLITE LED IP Strip 150 5m RGB 24V

Power supply:	24V DC
Power consumption:	30 W
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Fixed supply cord with open wires
Cable length:	Approx. 0,15 m
LED type:	150 x SMD 5050 3in1 TCL RGB (homogenous color mix)
Control:	System controller
Standing/fixation:	Self adhesive
Lamps/meter:	30 pc/pcs
Power/meter:	7,2 W
Lamps/tube:	150 pc/pcs
Lamp distance:	33 mm
Cutting mark:	17 cm
Luminous flux (Lumen) per meter:	300 lm/m
Housing color:	White
Dimensions:	Length: 500 cm Width: 1 cm

Height: 0,2 cm	
0,18 kg	
Class 0 (no noise at all)	
G	
	0,18 kg Class 0 (no noise at all)

### EUROLITE LED Strip RGB RF Controller

Power supply:	12/24V DC
Power consumption:	Max. 360 W 12 V DC
	Max. 720 W 24 V DC
	120 W 12 V DC per channal
	240 W 24 V DC per channal
Output current:	Max. 3 x 10 A per channal
Power connection:	Mains input via screw terminal
Power output:	4 x screw terminal
Battery:	Micro (AAA) (not included)
Control:	Wireless remote control
Range:	Range up to 20m
Carrier frequency:	433,920 MHz
Connections:	Signal via 2 x RJ-45 (F) mounting version
	Screw terminal
Dimensions:	Length: 9 cm
	Width: 9 cm
	Height: 2,4 cm
Weight:	0,29 kg
Dimensions:	Height: 2,2 cm

# EUROLITE LED Strip Wall Panel for RGB RF Controller

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1 W
Power connection:	Mains input via screw terminal
Range:	Range up to 20m
Carrier frequency:	433,920 MHz
Housing design:	Flush mounting Finery housing (optional)
Dimensions:	Length: 8,6 cm Width: 8,6 cm Depth: 3,4 cm
Weight:	0,13 kg

# EUROLITE Electr. LED Transformer, 24V, 2A

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class II

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Power connection:	Mains input via screw terminal
Power output:	Screw terminal
Housing color:	White matte
Controls:	Overload; short-circuit; overheat
Output:	24 V DC, stabilized; 2 A;
Material:	Plastic
Dimensions:	Length: 18 cm
	Width: 4 cm
	Height: 2,5 cm
Weight:	0,14 kg