

EUROLITE Set 4x LED CBB-4 COB RGB Bar + Case

4x LED light effect bar with RGB color mixing and IR remote control incl. PRO flightcase

Art. No.: 2000575

GTIN:



Features:

- 4 LEDs 23 W COB (chip-on-board) 3in1 R/G/B (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 19 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function
- Flicker-free
- With a beam angle of 39°
- With mounting bracket
- 4 digit 7-segment LED display
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; stage; clubs/dancing school; decoration; mobile djs / entertainer; video and photography
- Application possibility: Standing; suspended; on stand
- <p>ROADINGER Flightcase 4x LED CBB-4
- <h2 class="featureSatz">Trunk case, PRO version</h2>With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Hinged, chromium plated case handle
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware

Logistic

- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 17.44 kg

EUROLITE LED CBB-4 COB RGB Bar

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 70 W |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x IEC connector (F) mounting version |
| Fuse: | T 1 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 4 x 23 W COB (chip-on-board) 3in1 R/G/B (homogenous color mix) |
| Flash rate: | 0.3 - 23 Hz |
| DMX channels: | 3; 5; 12; 15; 19 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | 1 x low-noise cooling fan |
| Control: | Stand-alone; DMX; IR remote control; sound to light via microphone; master/slave function |
| Fixtures available for: | Light´J; LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief |
| Projection: | Flicker-free |
| Beam angle (1/2 peak): | 39° |
| Beam angle (1/10 peak): | 70° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Length: 46 cm Depth: 16 cm Height: 16 cm |
| Weight: | 3.97 kg |
| Noise classification: | Class 2 (slight noise) |
| Diameter mounting holes: | 3 x Ø11mm; 4 x Ø8mm |
| Material: | Metal, 2.5 mm |
| Cable construction: | 3 x 0.75 mm ² H05VV-F |
| Cable length: | Approx. 1.1 m |

| | |
|------------------|---|
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x LED CBB-4

| | |
|--------------------------|---|
| Maximum load: | 25 kg |
| Aluminum profile frames: | 25 mm |
| Case handle: | 1 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm; birch multiplex |
| Color: | Black, laminated; dark brown, laminated |
| Device compartment: | 46.5 cm x 11.5 cm x 17 cm |
| Accessory compartment: | 48 cm x 8 cm x 17 cm |
| Inside dimensions: | 54 cm x 48 cm x 17 cm |
| Dimensions: | Width: 68 cm Depth: 53 cm Height: 27 cm |
| Weight: | 9.55 kg |

Scope of delivery:

- 1 x spotlight
- 1 x power cord
- 1 x remote control
- 1 x battery
- 1 x user manual