

EUROLITE Set 8x LED 7C-7 Silent Slim Spot + Case

8x inaudible 7in1 PAR spotlight in a space-saving design including PRO flightcase

Art. No.: 2000582

GTIN:



List price: 2438.31 €

incl. 19% VAT.

Features:

EUROLITE LED 7C-7 Silent Slim Spot

Silent 7in1 LED PAR spotlight in a space-saving design

- Flat version requires minimal space when mounting
- 7 powerful LEDs 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix)
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 15°
- Very high color rendering index (CRI)
- With double bracket
- 4 digit 7-segment LED display
- Color blend stepless; Dimmer electronic
- Silent operation
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; Wedding/gala/events; Stage; theater; mobile djs / entertainer
- Application possibility: Standing; suspended; on stand

Package contents

- 1 x light effect, 1 x power cord, 1 x remote control, 1 x user manual

Logistic

ROADINGER Flightcase 8x SLS Size M

Trunk case, PRO version

- Individually adjustable and removable dividers for universal use
- With 8 Device compartments
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 1 high-quality butterfly lock
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 36,65 kg

EUROLITE LED 7C-7 Silent Slim Spot

| | |
|------------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 45 W |
| IP classification: | IP20 |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | 1 x P-Con (gray), mounting version |
| Fuse: | 5 x 20 mm, T 1 A Fuse replaceable |
| Lamp type: | LED lamp |
| LED: | 7 x 9 W high-power 7in1 SCL RGB/CW/WW/A/UV (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 3; 4-1; 4-2; 4-3; 4-4; 5; 6; 7; 9; 12 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| Control: | Stand-alone; DMX; IR remote control; Sound to light via Microphone; Master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| Beam angle: | 15° |
| Beam angle (1/2 peak): | 15° |
| Beam angle (1/10 peak): | 33° |
| Color rendering index (CRI): | 92 Ra |

| | |
|--------------------------|---|
| Housing color: | Black |
| Attachment system: | Double bracket |
| Display type: | 4 digit 7-segment LED display |
| USB port: | Typ A |
| Material: | Aluminum casting; metal |
| Dimensions: | Width: 22 cm Depth: 11 cm Height: 25,5 cm |
| Weight: | 2,60 kg |
| Noise classification: | Class 0 (no noise at all) |
| Photobiological safety: | Risk Group 0 |
| Power cord | |
| Cable construction: | 3 x 1,0 mm ² H05VV-F |
| Cable length: | Approx. 1,2 m |
| Mounting bracket | |
| Diameter mounting holes: | 1 x Ø11mm |
| Material: | Metal, 2,5 mm |
| Remote control | |
| Battery: | 1 x Button cell 3.0 V CR2025 lithium manganese built-in |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 8x SLS Size M

| | |
|--------------------------|---|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 1 pc/pcs |
| Use of brands: | Branded hardware |
| Material: | Birch multiplex, 7 mm |
| Color: | Dark brown, laminated |
| Compartment dimensions: | 11,5 cm x 24 cm x 34 cm |
| Inside dimensions: | 46 cm x 48 cm x 34 cm |
| Dimensions: | Width: 53,5 cm Depth: 53,5 cm Height: 44,5 cm |
| Weight: | 13,35 kg |