



Features:

Logistic

EUROLITE LED TMH-X7 Moving-Head Wash Zoom

Compact washlight, 7 intense 25 W LEDs (7in1), unique color mixing

- Equipped with seven 25 W LEDs in the colors red, green, blue, amber, white, lemon and UV
- Positioning within 540° PAN and 270° TILT
- Stepless RGBAWL+UV color mixture
- Color change with diverse settings
- Color presets
- Dimmer
- Dimmer speed (step response) adjustable
- Motorized zoom with 3-34° beam angle
- Sound-control via built-in microphone; sensitivity adjustable
- Strobe effect with adjustable speed, random strobe effect
- Automatic position correction
- Exact positioning via 16 bit PAN/TILT movement resolution
- PAN angle switchable between 540° and 360°
- DMX-controlled operation or stand-alone operation with Master/Slave function
- Control board with color LCD for adjusting the DMX-starting address, PAN/TILT Reverse, Reset
- Switch-mode power supply for operation between 100 and 240 volts
- Power connection via P-Con jack and included power cable with safety plug
- 7 LEDs 25 W high-power 7in1 RGBWAL/UV (homogenous color mix)
- Positioning within 540° PAN, 270° TILT

- PAN angle switchable between 540° and 360°
- Auto position correction (feedback)
- Exact positioning (16 bit resolution)
- Zoom motor driven
- The device is cooled by temperature-controlled fan
- Control via DMX; stand-alone; sound to light via microphone
- Flicker-free

ROADINGER Flightcase 4x LED TMH-X7 Moving head

Trunk case with castors, PRO version

- With accessory compartment
- With 4 device compartments
- High-quality workmanship with birch multiplex 7 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Closes with a
- 4 x castors with 2 locking brakes
- 4 x built-in stacking trays in the cover
- Branded hardware
- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 68.00 kg

EUROLITE LED TMH-X7 Moving-Head Wash Zoom

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	135 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	1 x P-Con (gray), mounting version
Lamp type:	LED lamp
LED type:	7 x 25 W high-power 7in1 RGBWAL/UV (homogenous color mix)
Max. TILT movement:	270° exact positioning (16 bit resolution) auto position correction (feedback)
Max. PAN movement:	540°, 360° exact positioning (16 bit resolution) auto position correction (feedback)
Flash rate:	0 - 18 Hz
Equipment:	Zoom motor driven
DMX channels:	20
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan

Control:	DMX; stand-alone; sound to light via microphone
Fixtures available for:	Light J; LED PC-Control 512; Light Captain
Projection:	Flicker-free
Beam angle (1/2 peak):	3 - 34°
Beam angle (1/10 peak):	8 - 55°
Illuminance in Lux (lx):	Narrow red (R) 3m: 779 lx, 6m: 193 lx Wide red (R) 3m: 64 lx, 6m: 19 lx Narrow green (G) 3m: 1936 lx, 6m: 489 lx Wide green (G) 3m: 163 lx, 6m: 48 lx Narrow blue (B) 3m: 339 lx, 6m: 87 lx Wide blue (B) 3m: 29 lx, 6m: 9 lx Narrow cold white (CW) 3m: 2178 lx, 6m: 555 lx Wide cold white (CW) 3m: 183 lx, 6m: 55 lx Narrow amber (A) 3m: 732 lx, 6m: 182 lx Wide amber (A) 3m: 60 lx, 6m: 18 lx Narrow ultra violet (UV) 3m: 20 lx, 6m: 5 lx Wide ultra violet (UV) 3m: 2 lx, 6m: 0 lx Narrow lime 3m: 1780 lx, 6m: 455 lx Wide lime 3m: 148 lx, 6m: 45 lx Narrow all 3m: 6778 lx, 6m: 1719 lx Wide all 3m: 561 lx, 6m: 168 lx
Housing color:	Black
Dimensions:	Width: 29.1 cm Depth: 23.1 cm Height: 41.1 cm
Weight:	10.10 kg
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x LED TMH-X7 Moving head

Aluminum profile frames:	25 mm
Case handle:	4 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes 4 x built-in stacking trays in the cover
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm; birch multiplex
Color:	Black, laminated; dark brown, laminated
Device compartment:	45 cm x 20 cm x 33.5 cm
Middle compartment:	10.5 cm x 61 cm x 33.5 cm
Inside dimensions:	100.5 cm x 61 cm x 33.5 cm
Dimensions:	Width: 107 cm Depth: 63 cm Height: 65 cm
Weight:	27.55 kg

Scope of delivery:

1 x moving light
1 x user manual
1 x power cord
2 x omega bracket
1 x XLR cable