

EUROLITE Set LED SL-400 DMX Search Light + Case

Follow spot with warm white 300 W LED including PRO flightcase

Art. No.: 2000608

GTIN: 4026397659085



Features:

- Manual control via control panel with buttons and faders
- 1 LED 300 W COB (chip-on-board) warm white (WW)
- Focus manual; iris stepless
- Dimmer electronic
- Strobe effect
- Color wheel with 5 dichroic filters plus open half colors selectable
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX
- Flicker-free
- Direct color temperature selection for 4 preset values
- Good color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- Built with SEETRONIC connector
- Suitable for a range of use from 25 to 50 meters
- For application areas such as: Wedding/gala/events; stage; theater; rental
- Application possibility: Suspended; on stand
- ROADINGER Flightcase 1x LED SL-400
- Trunk case, PRO version With 1 device compartment
- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated
- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- Branded hardware

Logistic

EAN / GTIN: 4026397659085

Weight: 24,30 kg

Length: 0.60 m

Width: 0.90 m

Height: 0.60 m

Bulky product

- Made in Europe
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 22.00 kg

EUROLITE LED SL-400 DMX Search Light

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	440 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Lamp type:	LED lamp
LED type:	1 x 300 W COB (chip-on-board) warm white (WW)
Flash rate:	0.8 - 16 Hz
Equipment:	Focus manual; iris stepless
Color generation:	Color wheel with 5 dichroic filters plus open Half colors selectable
DMX channels:	6
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX
Fixtures available for:	LED PC-Control 512; Light Captain
Projection:	Flicker-free
PWM frequency:	26600 Hz
Beam angle (1/2 peak):	7 - 13°
Beam angle (1/10 peak):	3 - 17°
Color temperature:	3500K
Color rendering index (CRI):	80 Ra
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	4 digit 7-segment LED display
Use of brands:	Built with SEETRONIC connector
Range of use:	25m - 50m
Dimensions:	Length: 77 cm Width: 27 cm Height: 29 cm
Weight:	12.35 kg
Noise classification:	Class 2 (slight noise)
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 1x LED SL-400

Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Device compartment:	85 cm x 28.5 cm x 36.5 cm
Inside dimensions:	85 cm x 36.5 cm x 20 cm
Dimensions:	Width: 89 cm Depth: 32 cm Height: 41 cm
Weight:	10.00 kg

Scope of delivery:

- 1 x spotlight
- 1 x user manual
- 1 x power cord
- 1 x XLR cable
- 1 x mounting bracket
- 1 x hex key