



**The article is no longer in our assortment.**

#### Features:

##### **OMNITRONIC MOM-10BT4 Receiver Module**

Receiver module for UHF frequencies (microphone, bodypack + audio link module)

- For retrofitting the MOM-10BT4 modular PA system
- Up to 4 receiving modules can be retrofitted
- 16 selectable UHF frequencies (823-832 and 863-865 MHz)
- LEDs for power, carrier and audio signals
- Operating range up to 30m with line-of-sight
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- UHF 863 - 865 MHz License-free and approved in Europe

##### **Package contents**

- 1 x receiver, 1 x user manual, 1 x declaration of conformity

#### Logistic

##### **OMNITRONIC MOM-10BT4 Audio Link Module**

Transmitter module for audio transmission to MOM-10BT4 PA systems

- For retrofitting the MOM-10BT4 modular PA system
- For wireless audio transmission to receiving units of MOM-10BT4 PA systems (audio link mode)
- 1 audio link module can be retrofitted
- Transmission of the master in mono or stereo R
- 16 selectable UHF frequencies (823-832 and 863-865 MHz)
- Detachable BNC antenna
- Operating range up to 30m with line-of-sight
- UHF 823 - 832 MHz License-free and approved in large parts of Europe
- UHF 863 - 865 MHz License-free and approved in Europe

##### **Package contents**

- 1 x transmitter, 1 x antenna, 1 x user manual, 1 x declaration of conformity

## Technical specifications:

---

Weight:	0,21 kg
---------	---------

---

### OMNITRONIC MOM-10BT4 Receiver Module

Type:	Receiver
Power supply:	12V DC 150 mA
Frequency range:	50 - 15000 Hz
S/N ratio:	>80 dB
THD:	<0,1 % at 1 kHz
Sensitivity:	-95 dB
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Frequency stability:	± 0,01 %
Frequency selection:	16 switchable frequencies
Control elements:	Frequency selector switch, level control
Dimensions:	Width: 7,1 cm Depth: 13,9 cm Height: 3 cm
Weight:	0,09 kg

### OMNITRONIC MOM-10BT4 Audio Link Module

Type:	Transmitter
Power supply:	12V DC 150 mA
Range:	Range up to 30m with line-of-sight
Frequency band:	UHF 823 - 832 MHz; UHF 863 - 865 MHz
Frequency stability:	± 0,01 %
RF power output:	10 mW
Frequency selection:	16 switchable frequencies
Control elements:	Frequency selector switch, level control
Status LED:	Power, signal
Connections:	Output: antenna via 1 x BNC (F)
Dimensions:	Width: 7,1 cm Depth: 13,9 cm Height: 3 cm
Weight:	0,12 kg