

EUROLITE Set 4x AKKU TL-3 TCL white + Case with charging function

4x white spot for lighting within trussing, 3 x 3 W 3in1 LED incl. PRO flightcase with charging function

Art. No.: 20000650

GTIN: 4026397670875



List price: 1129.31 €

incl. 19% VAT.

Features:

EUROLITE AKKU TL-3 TCL Trusslight QuickDMX wh

Spot for lighting within trussing, 3 x 3 W 3in1 LED, QuickDMX transceiver

- Compact and bright
- Ideal for ALUTRUSS DECOLOCK DQ3 3-point system
- Integrated QuickDMX transceiver for wireless DMX control
- Threaded inserts for suspended installation
- Cordless, flexible and versatile
- Battery operation up to 16h depending on program used
- 3 powerful LEDs 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
- Dimmer electronic; color blend stepless; color change adjustable; Dimmer speed (step response) adjustable
- Strobe effect
- The device is cooled by passive convection cooling
- Control via IR remote control; DMX; QuickDMX; sound to light via microphone; stand-alone
- Preprogrammed in Light'J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
- Flicker-free
- With a beam angle of 11°
- Multicolor LCD display
- Mains input and output for power linking up to 8 units
- For application areas such as: Small rental; wedding/gala/events; mobile djs / entertainer; stage
- Silent operation
- Application possibility: Standing; suspended

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x remote control, 1 x battery, 1 x declaration of conformity

Logistic

EAN / GTIN: 4026397670875

Weight: 14,50 kg

Length: 0.82 m

Width: 0.41 m

Height: 0.35 m

ROADINGER Flightcase 4x AKKU TL-3 Trusslight QuickDMX with charging function

Trunk case

- With 4 device compartments
- With accessory compartment
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- For further information about this product, please refer to the Data Sheet under "Downloads"

Package contents

- 1 x device, 1 x power cord, 1 x user manual

Technical specifications:

Weight:	14,30 kg
---------	----------

EUROLITE AKKU TL-3 TCL Trusslight QuickDMX wh

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	25 W
IP classification:	IP20
Power connection:	Battery/battery pack Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Cable length:	Approx. 1,2 m
Power output:	1 x IEC connector (F) mounting version
Battery pack type:	1 x lithium ion 11,1 V, 4400 mAh, 48,84 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 3h
Lamp type:	LED lamp
LED type:	3 x 3 W SMD 8072 3in1 TCL RGB (homogenous color mix)
Flash rate:	0 - 23 Hz
DMX channels:	3; 5; 8
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; DMX; QuickDMX; sound to light via microphone; stand-alone
Preprogrammed in:	Light´J; LED PC-Control 512; Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Colorchief
Projection:	Flicker-free
Carrier frequency:	2,4 GHz

Beam angle:	11°
Beam angle (1/2 peak):	11°
Beam angle (1/10 peak):	24°
Housing color:	White
Display type:	Multicolor LCD display
Dimensions:	Width: 12,1 cm Depth: 10,8 cm Height: 14,5 cm
Weight:	1,30 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 4x AKKU TL-3 Trusslight QuickDMX with charging function

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	Max. 1150 W
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Device fuse:	5 x 20 mm, T 5 A fuse replaceable
Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs with shut-off function
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Compartment dimensions:	15,5 cm x 15,5 cm x 11,5 cm
Accessory compartment:	9 cm x 34 cm x 11,5 cm
Dimensions:	Width: 57 cm Depth: 37 cm Height: 24,5 cm
Weight:	9,10 kg