

OMNITRONIC Set TRM-202MK3 + Case

2-channel rotary mixer with 3-band frequency isolator for DJs including PRO flightcase

Art. No.: 2000666

GTIN: 4026397591743



List price: 593.81 €

incl. 19% VAT.

Features:

OMNITRONIC TRM-202MK3 2-Channel Rotary Mixer

2-channel rotary mixer with 3-band frequency isolator for DJs

- Classic rotary mixer with 2 input channels and integrated 3-band frequency isolator for DJs
- Gain control, 2-way equalizer (highs/lows) and phono/line switching per channel
- Dedicated boost and kill cut
- Kill cut feature allows DJs to completely remove low, mid and high frequencies for amazing mixing
- Classic ALPS potentiometers (Blue Velvet RK27)
- High-grade components ensure long life and excellent sound quality
- DJ microphone input with separate level control
- Prefader listening to input channels and the master output via adjustable headphones output, with cue mix/split function
- 12-digit stereo LED level meter and master level control
- Booth output with separate level control
- Outputs: master and booth (XLR/RCA L/R), record (stereo RCA)
- Desktop console housing
- For application areas such as: Clubs/dancing school; mobile use; mobile djs / entertainer; homerecording and studios

Package contents

- 1 x device, 1 x power cord, 1 x user manual

ROADINGER Flightcase TRM-202 MK3

Hood case, PRO version

- High-quality workmanship with birch multiplex 7 mm, dark brown, laminated

Logistic

EAN / GTIN: 4026397591743

Weight: 6,50 kg

Length: 0.61 m

Width: 0.31 m

Height: 0.40 m

- Interior with foam padding
- Aluminum profile frames 25mm with rounded edges
- Rugged carrying handle
- 2 high-quality butterfly locks
- Branded hardware
- Made in Europe

Technical specifications:

Weight: 5,88 kg

OMNITRONIC TRM-202MK3 2-Channel Rotary Mixer

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	6,5 W
Protection class:	Protection class I
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Frequency range:	20 - 20000 Hz Microphone 20 - 20000 Hz line 40 - 18000 Hz phono
S/N ratio:	>77 dB phono >80 dB Microphone >85 dB line
THD:	Line <0,03 % at 1 kHz Phono <0,1 % at 1 kHz
Gain:	Microphone 44 dB Line 20 dB Phono 60 dB to +75 dB
Isolators:	Master Gain: - ? bis +9 Low/mid 300 Hz, 18db/oct , Butterworth Mid/high 4000 Hz, 18db/oct , Butterworth
Control elements:	Power switch, source selector, Crossfader, Cue mix split function, tone control
Status LED:	Power, master level meter, chanal source, CUE, Microphone
Connections:	Input: line via 2 x stereo RCA Input: line/phono via 2 x stereo RCA Input: Microphone via 1 x 3-pin XLR Output: headphones via 1 x 6.3 mm jack socket (stereo) mounting version Output: rec. via 1 x stereo RCA Output: booth via 2 x 3-pin XLR Output: booth via 1 x stereo RCA Output: master via 2 x 3-pin XLR Output: master via 1 x stereo RCA
Channels:	Input chanel: 2 x stereo with Line-Line/Phono switch via RCA, channel control via Rotary, 2-band tone control EQ, CUE switch, Phono gain rotory, source selector

Microphon chanal: 1 x mono via XLR, channel control via Rotary dial, ON AIR switch

Booth output: 1 x stereo via XLR or RCA, channel control via Rotary dial

Master output: 1 x stereo via XLR or RCA, channel control via Rotary dial

Headphones output: 1 x stereo via Jack, channel control via Rotary dial, Cue mix split function

Max. level:	Output: +22 dBu
Material:	Metal
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 19 cm Depth: 25 cm Height: 10,7 cm
Weight:	2,68 kg

ROADINGER Flightcase TRM-202 MK3

Maximum load:	25 kg
Aluminum profile frames:	25 mm
Carrying handle:	1 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	Branded hardware
Material:	Birch multiplex, 7 mm
Color:	Dark brown, laminated
Dimensions:	Width: 24 cm Depth: 38 cm Height: 18 cm
Weight:	3,20 kg