

EUROLITE Set 8x LED PAR-64 COB RGBW 120W Zoom bk + Case

8x PAR spot with 120 W RGBW LED and manual zoom incl. flightcase with castors

Art. No.: 2000669

GTIN: 4026397126594



List price: 4937.31 €

incl. 19% VAT.

Features:

EUROLITE LED PAR-64 COB RGBW 120W Zoom bk

PAR spot with 120 W RGBW LED and manual zoom

- 1 powerful LED 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- 3 integrated show programs
- The device is cooled by temperature-controlled fan
- Control via stand-alone; DMX; Sound to light via Microphone; Master/slave function
- Flicker-free
- With a beam angle of 11° - 48°
- With Mounting bracket
- For application areas such as: Stage
- Color blend stepless; dimmer curves with adjustable response; pulse-width modulation variable
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3
- Mains input and output for power linking up to 8 units

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x xLR cable, 1 x filter frame, 1 x mounting bracket, 2 x knurled screw, 2 x washer

Logistic

EAN / GTIN: 4026397126594

Weight: 85,00 kg

Length: 1.20 m

Width: 0.80 m

Height: 1.20 m

Bulky product

ROADINGER Flightcase 8x PAR-64/ML-56

Trunk case with castors

- With 8 Device compartments
- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
cover with felt cover

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 72,90 kg

EUROLITE LED PAR-64 COB RGBW 120W Zoom bk

| | |
|-------------------------|--|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 140 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided) |
| Power output: | P-Con (gray), mounting version |
| Fuse: | F 2 A |
| Lamp type: | LED lamp |
| LED: | 1 x 120 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 4; 5; 9; 6 |
| DMX input: | 1 x 3-pin XLR (M) mounting version |
| DMX output: | 1 x 3-pin XLR (F) mounting version |
| Cooling: | Temperature-controlled fan |
| Control: | Stand-alone; DMX; Sound to light via Microphone; Master/slave function |
| Preprogrammed in: | LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light J; Light Captain; EASY SHOW 2; EASY SHOW 3 |
| Projection: | Flicker-free |
| Beam angle: | 11° - 48° |
| Beam angle (1/2 peak): | 11 - 35° |
| Beam angle (1/10 peak): | 15 - 48° |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Dimensions: | Width: 26 cm Depth: 43,5 cm Height: 37,5 cm |
| Weight: | 3,90 kg |
| Noise classification: | Class 2 (slight noise) |
| Legal specifications | |

| | |
|------------------|--|
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 8x PAR-64/ML-56

| | |
|--------------------------|--|
| Maximum load: | 50 kg |
| Aluminum profile frames: | 30 mm |
| Case handle: | 4 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs |
| Transport aid: | 4 x castors with 2 locking brakes |
| Material: | Plywood multi-layer glued, 9 mm |
| Color: | Black, laminated |
| Device compartment: | 24 cm x 24,5 cm x 42 cm |
| Inside dimensions: | 96 cm x 49 cm x 42 cm |
| Dimensions: | Width: 1,09 m Depth: 57,5 cm Height: 68,5 cm |
| Weight: | 41,70 kg |